SAFETY DATA SHEET

Q8 Formula Special FE 0W-20



SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier **Product name** : Q8 Formula Special FE 0W-20 1.2 Relevant identified uses of the substance or mixture and uses advised against Material uses : Lubricating oil for automotive engines 1.3 Details of the supplier of the safety data sheet **Supplier** : Q8Oils Italia S.r.l. Via Volpedo 2 15050 Castellar Guidobono (AL) Tel. +39 02-90595.1, Fax +39 02-90076347 e-mail: Q8OilsItalia@Q8.it **Manufacturer / Distributor** Q8Oils Italia S.r.l. Kuwait Petroleum Belgium N.V./S.A. 2 1 Via Volpedo 2 Petroleumkaai 7 15050 Castellar Guidobono (AL) B-2020 Antwerp Italy Belgium e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only. **PCN** Information contact : PCNinfo@Q8.com, communication preferably in English only. 1.4 Emergency telephone number Italy : 800 699 792 (Toll free) CARECHEM24 : +44 (0) 1235 239 670 Europe **Global (English only)** : +44 (0) 1865 407 333 National advisory body/Poison Center Italy : CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA (ROMA) : 06 68593726 Az. Osp. Univ. Foggia (FOGGIA) : 800183459 Az. Osp. "A. Cardarelli" (NAPOLI) : 081-5453333 CAV Policlinico "Umberto I" (ROMA) : 06-49978000 CAV Policlinico "A. Gemelli" (ROMA) : 06-3054343 Az. Osp. "Careggi" U.O. Tossicologia Medica (FIRENZE) : 055-7947819 CAV Centro Nazionale di Informazione Tossicologica (PAZIA): 0382-24444 Osp. Niguarda Ca' Granda (MILANO) : 02-66101029 Azienda Ospedaliera Papa Giovanni XXII (BERGAMO) : 800883300 Azienda Ospedaliera Integrata Verona (VERONA) : 800011858

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown : None. toxicity

Q8 Formula Special FE 0W-20

SECTION 2: Hazards identification

Ingredients of unknown : None. ecotoxicity

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	1	No signal word.
Hazard statements	1	No known significant effects or critical hazards.
Precautionary statements		
General	-	 P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1), Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts and methyl methacrylate. May produce an allergic reaction. Safety data sheet available on request.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Detergents - Regulation (EC) No 648/2004	1	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	1	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	In the provided a state of the provided and the provided a pro
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Severely refined mineral oil (C15 - C50) - H304	CAS: *	≥50 - ≤75	Asp. Tox. 1, H304	-	[1] [2]
Severely refined mineral oil (C15 - C50) - Not classified.	CAS: *	≥10 - ≤25	Not classified.	-	[2]
Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs.,	EC: 601-337-1 CAS: 114959-46-5	<1	Skin Sens. 1B, H317	-	[1]
Date of issue/Date of revision	: 12-10-2022 Dat	te of previous is	sue : 26-09-2019	Version :1.0	02 2/1

Q8 Formula Special FE 0W-20

SECTION 3: Composition/information on ingredients					
calcium salts (2:1)					
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	EC: 682-816-2 CAS: 722503-68-6	<1	Skin Sens. 1B, H317	-	[1]
methyl methacrylate	REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6	≤0.3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25

CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29

CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

CAS: 64742-56-9, EC: 265-159-2, EU REACH: 01-2119480132-48

CAS: 1335203-17-2, EC: 934-956-3, EU REACH: 01-2119827000-58

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed			
<u>Over-exposure signs/sy</u>	<u>mptoms</u>		
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking		
Ingestion	: No specific data.		
4.3 Indication of any imm	ediate medical attention and special treatment needed		
Notes to physician	 Freat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 		
Specific treatments	: No specific treatment.		

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use dry chemical, CO_2 , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising f	rom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	

Date of issue/Date of revision

SECTION 6: Accidental release measures

6.3 Methods and material	s for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling			
Protective measures	: Put on appropriate personal protective equipment (see Section 8).		
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.		

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Severely refined mineral oil (C15 - C50) - H304	EU OEL (Europe).
	TWA: 5 mg/m ³ 8 hours. Form: Mist
	STEL: 10 mg/m ³ 15 minutes. Form: Mist
Severely refined mineral oil (C15 - C50) - Not	EU OEL (Europe).
classified.	TWA: 5 mg/m ³ 8 hours. Form: Mist
	STEL: 10 mg/m ³ 15 minutes. Form: Mist
methyl methacrylate	Ministry of Labour and Social Policy (Italy, 6/2020). Short Term: 100 ppm 15 minutes. 8 hours: 50 ppm 8 hours.
Date of issue/Date of revision : 12-10-2022 Date	ate of previous issue : 26-09-2019 Version : 1.02 5/15

SECTION 8: Exposure controls/personal protection

	EU OEL (Europe, 10/2019). Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.
Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Benzoic acid, 2-hydroxy-, mono- C14-18-alkyl derivs., calcium salts (2:1)	DNEL	Long term Oral	0.25 mg/ kg bw/day	General population	Systemic
()	DNEL	Long term Dermal	0.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic
methyl methacrylate	DNEL	Long term Dermal	8.2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	13.67 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	74.3 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	104 mg/m ³	General population	Local
	DNEL	Long term Inhalation	208 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	208 mg/m ³	Workers	Systemic
	DNEL	Short term Dermal	1.5 mg/cm ²	General population	Local
	DNEL	Long term Dermal	1.5 mg/cm ²	General population	Local
	DNEL DNEL	Short term Dermal Long term Dermal	1.5 mg/cm ² 1.5 mg/cm ²	Workers	Local Local
	DNEL	Long term Oral	8.2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	208 mg/m ³	General population	Local
	DNEL	Short term Inhalation	416 mg/m ³	Workers	Local

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Date of issue/Date of revision

: 12-10-2022 Date of previous issue

Q8 Formula Special FE 0W-20

SECTION 8: Exposure controls/personal protection

Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working pe Appropriate techniques should be used to remove potentially contaminated clo Wash contaminated clothing before reusing. Ensure that eyewash stations an safety showers are close to the workstation location.	othing.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a assessment indicates this is necessary to avoid exposure to liquid splashes, m gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses side-shields.	nists,
Skin protection		
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard s be worn at all times when handling chemical products if a risk assessment ind this is necessary. Wear suitable gloves tested to EN374. Recommended: < * hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.	icates 1
Body protection	Personal protective equipment for the body should be selected based on the tabe being performed and the risks involved and should be approved by a specialis before handling this product.	
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should approved by a specialist before handling this product.	l be
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °AX1; Hot material: A1P2.	ı ortant
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislati In some cases, fume scrubbers, filters or engineering modifications to the proceed equipment will be necessary to reduce emissions to acceptable levels.	

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Clear.]
Appearance	: Oily liquid.
Color	: Yellow
Odor	: Characteristic. [Slight]
Odor threshold	: Not available.
Melting point/freezing point	: 🗾 📈 45°C (<-49°F) [ASTM 5950]
Pour point	: 🗾 🗹 45°C (<-49°F) [ASTM 5950]
Initial boiling point and boiling range	: >300°C (>572°F)
Flammability	: Not applicable.
Lower and upper explosion limit	: Not available.
Flash point	: Open cup: 222°C (431.6°F) [ASTM D92.]
Auto-ignition temperature	: >300°C (>572°F)
Decomposition temperature	: Not available.
рН	: Not applicable.
Viscosity	 Kinematic (40°C (104°F)): 40.9 mm²/s (40.9 cSt) Kinematic (100°C (212°F)): 8.1 mm²/s (8.1 cSt)
Date of issue/Date of revision	: 12-10-2022 Date of previous issue : 26-09-2019

SECTION 9: Physical and chemical properties

Solubility(ies)

Solubility(ies)	1	
Media		Result
old water hot water		Not soluble Not soluble
Partition coefficient: n-octano	1/:	Not applicable.
Vapor pressure	:	<mark>≮</mark> 0.01 kPa (<0.075006 mm Hg)
Density	1	Ø.85 g/cm³ [15°C (59°F)] [ASTM D 4052]
Vapor density	:	Not available.
Explosive properties	1	Not applicable.
Oxidizing properties	1	Not applicable.
Particle characteristics		
Median particle size	1	Not applicable.

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: The product is stable.				
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: No specific data.				
10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials				
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.				

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil	LC50 Inhalation Dusts and	Rat - Male,	5.53 mg/l	4 hours
(C15 - C50) - H304	mists	Female		
(, , , , , , , , , , , , , , , , , , ,	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Severely refined mineral oil	LC50 Inhalation Dusts and	Rat - Male,	5.53 mg/l	4 hours
(C15 - Ć50) - Not classified.	mists	Female	5	
,	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1)	LD50 Oral	Rat	>5000 mg/kg	-
methyl methacrylate	LC50 Inhalation Vapor	Rat	78000 mg/m ³	4 hours
, ,	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	7872 mg/kg	-

Acute toxicity estimates

Q8 Formula Special FE 0W-20

SECTION 11: Toxicological information

		•		•	•
Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Severely refined mineral oil (C15 - C50) - H304 Severely refined mineral oil (C15 - C50) - Not classified. methyl methacrylate	N/A N/A 7872	N/A N/A N/A	N/A N/A N/A	N/A N/A 78	5.53 5.53 N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Severely refined mineral oil (C15 - C50) - H304	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
Severely refined mineral oil (C15 - C50) - Not classified.	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days

Conclusion/Summary : Not available.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Severely refined mineral oil (C15 - C50) - H304	skin	Guinea pig	Not sensitizing
Severely refined mineral oil (C15 - C50) - Not classified.	skin	Guinea pig	Not sensitizing

Conclusion/Summary : Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Severely refined mineral oil (C15 - C50) - H304	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
Severely refined mineral oil (C15 - C50) - Not classified.	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

Conclusion/Summary : Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - H304	Negative - Dermal - TC	Mouse - Female	-	78 weeks
Severely refined mineral oil (C15 - C50) - Not classified.	Negative - Dermal - TC	Mouse - Female	-	78 weeks
	· Net evellele	•		

Conclusion/Summary

: Not available.

Reproductive toxicity

Q8 Formula Special FE 0W-20

SECTION 11: Toxicological information

	5					
Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - H304	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-
Severely refined mineral oil (C15 - C50) - Not classified.	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-
Conclusion/Summary	: Not availa	able.				•

Conclusion/Summary

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) - H304	Negative - Dermal	Rat	2000 mg/kg	7 days per week
Severely refined mineral oil (C15 - C50) - Not classified.	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methyl methacrylate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result	
Severely refined mineral oil (C15 - C50) - H304	ASPIRATION HAZARD - Category 1	

Information on the likely routes of exposure	:	Not available.
Potential acute health effects	<u>s</u>	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the phy	/sic	cal, chemical and toxicological characteristics
Eye contact	1	No specific data.
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation dryness cracking
Ingestion	:	No specific data.
Delayed and immediate effect	<u>ts</u>	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Date of issue/Date of revision		: 12-10-2022 Date of previous issue : 26-09-2019 Version : 1.02

10/15

SECTION 11: Toxicological information

Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure	
Severely refined mineral oil (C15 - C50) - H304	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day	
、 ,	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week	
	Sub-acute NOAEL Inhalation	Rat - Male	>980 mg/m ³	4 weeks; 5 days per week	
Severely refined mineral oil (C15 - C50) - Not classified.	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day	
	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week	
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m³	4 weeks; 5 days per week	
Conclusion/Summary	: Not available.				
General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and, or dermatitis.				
Carcinogenicity	: No known significant effects or critical hazards.				
Mutagenicity	: No known significant effects or critical hazards.				
Reproductive toxicity	: No known significant effects	: No known significant effects or critical hazards.			

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Severely refined mineral oil (C15 - C50) - H304	Acute NEL >100 mg/l Fresh water	Algae	72 hours
· · · · · ·	Acute NEL >10000 mg/l Fresh water	Daphnia - Daphnia Magma	48 hours
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days
Severely refined mineral oil (C15 - C50) - Not classified.	Acute NEL >100 mg/l Fresh water	Algae	72 hours
	Acute NEL >10000 mg/l Fresh water	Daphnia - Daphnia Magma	48 hours
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days
methyl methacrylate	Acute LC50 130000 μg/l Fresh water	Fish - Pimephales promelas - Adult	96 hours
Conclusion/Summary	: Not available.	1	1

12.2 Persistence and degradability

Conclusion/Summary : Not available.

SECTION 12: Ecological information			
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Severely refined mineral oil (C15 - C50) - H304 Severely refined mineral oil (C15 - C50) - Not classified.	-	-	Inherent Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Benzoic acid, 2-hydroxy-, mono-C14-18-alkyl derivs., calcium salts (2:1)	5.32	23442	high
methyl methacrylate	1.38	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product		
Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:	Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
Packaging		
Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	:	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Q8 Formula Special FE 0W-20

SECTION 14: Transport information

	•					
	ADR/RID	ADN	IMDG	IATA		
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.		
14.2 UN proper shipping name	-	-	-	-		
14.3 Transport hazard class(es)	-	-	-	-		
14.4 Packing group	-	-	-	-		
14.5 Environmental hazards	No.	No.	No.	No.		

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Other EU regulations		
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed
Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed
Ozone depleting substand Not listed.	<u>es</u>	<u>(1005/2009/EU)</u>
Prior Informed Consent (P Not listed.	<u>(OIC)</u>	<u>(649/2012/EU)</u>

Q8 Formula Special FE 0W-20

SECTION 15: Regulatory information

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

D.Lgs. 152/06	: Not determined.
D.Lgs. 81/2008	: Health and Safety in the workplace.
D.Lgs. 25/2002	: Protection against risks from chemical agents.
D.Lgs. 65/2003	: Classification Labelling and Packaging of Dangerous Products.
D.M. 14/01/2008	: List of work related deseases that require notification.
Hazard class for water (WGK)	: 1
VOC content	: Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	:	All components are listed or exempted.
Canada	1	All components are listed or exempted.
China	1	Not determined.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	1	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	Al components are listed or exempted.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	;	Not determined.
15.2 Chemical Safety Assessment	:	This product contains substances for which Chemical Safety Assessments are still required.

Q8 Formula Special FE 0W-20

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

⊮ 225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Full text of classifications [CLP/GHS]

Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Training advice	: Ensure operatives are trained to minimise exposures.
Date of printing	: 12-10-2022
Date of issue/ Date of	: 12-10-2022
revision	
Date of previous issue	e : 26-09-2019
Version	: 1.02
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands
Notice to reader	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.