

Q8 Formula Techno FE 5W-30

Synthetic ACEA A5/B5 (Ford) passenger car engine oil

Description

Q8 Formula Techno FE 5W-30 is a passenger car engine oil for outstanding performance. It is also suitable for light duty commercial vehicles. This product provides fuel economy improvement up to 2,5% and outstanding protection against corrosion. It is designed for recent generation Ford Diesel and Gasoline engines meeting Euro 5 & Euro 6 emission legislation.

Applications

Q8 Formula Techno FE 5W-30 is designed for Ford engines, requiring specification WSS M2C 913-D, and is backwards compatible with all engines requiring Ford WSS M2C 912-A, 913-A/B & 913-C. It meets the requirements of ACEA A5/B5.

Specifications, recommendations and approvals

ACEA	A5/B5	Ford	M2C913-B
Fiat	9.55535-G1	Ford	M2C913-C
Ford	M2C912	Ford	M2C913-D
Ford	M2C913-A	Renault	RN 0700

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,85
Viscosity Grade	-	-	SAE 5W-30
Kinematic Viscosity, 40 °C	D 445	mm²/s	52.3
Kinematic Viscosity, 100 °C	D 445	mm²/s	9.7
Viscosity Index	D 2270	-	171
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=2.9
Apparent Viscosity, -30 °C	D 5293	mPa.s	4700
Pour Point	D 97	°C	-36
Flash Point, COC	D 92	°C	215

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Techno FE 5W-30 is **1.36** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here

