SAFETY DATA SHEET

Q8 Verdi 5



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : Q8 Verdi 5 **Viscosity or Type** : ISO VG 5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Lubricating oil for industrial systems

1.3 Details of the supplier of the safety data sheet

: Kuwait Petroleum Companies in the Benelux **Supplier**

Company Office: Desguinlei 100 - 8, 2018 Antwerp, Belgium Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium

Tel. +32 3 247 38 11, Fax +32 3 216 03 42

: Kuwait Petroleum Belgium N.V./S.A. **Manufacturer / Distributor**

Petroleumkaai 7

B-2020 Antwerp

Belgium

Q80ils Italia S.r.I. Via Volpedo 2

15050 Castellar Guidobono (AL)

e-mail address of person

responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only. **PCN** Information contact : PCNinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Europe : +44 (0) 1235 239 670 : +44 (0) 1865 407 333

Global (English only) National advisory body/Poison Center

: Poison Centre: +32 (0)70 245 245 **Belgium**

CARECHEM24

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

ASPIRATION HAZARD H304 Category 1 AQUATIC HAZARD (LONG-TERM) H412 Category 3

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown

toxicity

: None.

Ingredients of unknown : None.

ecotoxicity

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Date of issue/Date of revision : 08-04-2025 : 08-11-2022 Version : 1.06 1/17 Date of previous issue

SECTION 2: Hazards identification

Signal word : Danger

: H304 - May be fatal if swallowed and enters airways. **Hazard statements**

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P273 - Avoid release to the environment.

: P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or Response

doctor. Do NOT induce vomiting.

Storage : Not applicable.

: P501 - Dispose of contents and container in accordance with all local, regional, **Disposal**

national and international regulations.

Hazardous ingredients

Supplemental label

elements

: Severely refined mineral oil (C15 - C50) * - H304

: Not applicable.

Annex XVII - Restrictions on the manufacture. placing on the market and use of certain dangerous substances, mixtures and articles

: Not applicable.

Special packaging requirements

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Severely refined mineral oil (C15 - C50) * - H304	-	≥90	Asp. Tox. 1, H304	-	[1] [2]
2,6-di-tert-butylphenol	REACH #: 01-2119490822-33 EC: 204-884-0 CAS: 128-39-2	<1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
Distillates (petroleum), hydrotreated light naphthenic	REACH #: 01-2119480375-34 EC: 265-156-6 CAS: 64742-53-6 Index: 649-466-00-2	≤0.1	Asp. Tox. 1, H304	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

Date of issue/Date of revision : 08-11-2022 : 08-04-2025 Version : 1.06 2/17 Date of previous issue

SECTION 3: Composition/information on ingredients

Contains one or more of the following:

CAS: 1335203-17-2, EC: 934-956-3, EU REACH: 01-2119827000-58 CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29 CAS: 72623-86-0, EC: 276-737-9, EU REACH: 01-2119474878-16

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Skin contact: Wash skin thoroughly with soap and water or use recognized skin cleanser.

Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out

mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : Adverse symptoms may include the following:

nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 3/17

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Date of issue/Date of revision : 08-04-2025 : 08-11-2022 Date of previous issue Version: 1.06

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Severely refined mineral oil (C15 - C50) * -	EU OEL (Europe)
H304	TWA 8 hours: 5 mg/m³. Form: Mist.
	STEL 15 minutes: 10 mg/m³. Form: Mist.
Distillates (petroleum), hydrotreated light	Limit values (Belgium, 12/2023) [Olie]
naphthenic	TWA 8 hours: 5 mg/m³. Form: mist.
	STEL 15 minutes: 10 mg/m³. Form: mist.
	EU OEL (Europe)
	TWA: 5 mg/m³ (oil Mist).

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 5/17

SECTION 8: Exposure controls/personal protection

Product/ingredient name

2,6-di-tert-butylphenol

Result

DNEL - General population - Long term - Oral

6.75 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal

6.75 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

11.25 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

20.9 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation

70.61 mg/m³
<u>Effects</u>: Systemic

Distillates (petroleum), hydrotreated light naphthenic

DNEL - General population - Long term - Oral

0.74 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Dermal

0.97 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

1.19 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

2.73 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation

5.58 mg/m³ Effects: Local

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Do not ingest. If swallowed then seek immediate medical assistance.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 6/17

SECTION 8: Exposure controls/personal protection

Hand protection

Ehemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Sased on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2. Gas and combination filter cartridges should comply with the European standard EN14387.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Oily liquid.]

Appearance : Clear

Color : Yellow [Light]
Odor : Characteristic
Odor threshold : Not available.

Melting point/freezing point : Not applicable.

Pour point : <-12°C (<10.4°F) [ASTM D 97]

Boiling point or initial boiling

point and boiling range

: >260°C (>500°F)

Flammability
Lower and upper explosion

limit

Not applicable.Not available.

Auto-ignition temperature : >230°C (>446°F)

Decomposition temperature : >260°C

pH : Not applicable.

Viscosity : Kinematic (40°C (104°F)): 5 mm²/s (5 cSt) [ASTM D 445]

Kinematic (100°C (212°F)): 1.67 mm²/s (1.67 cSt) [ASTM D 445]

Solubility :

Media	Result
cold water	Not soluble
hot water	Not soluble

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 7/17

Q8 Verdi 5

SECTION 9: Physical and chemical properties

Partition coefficient n-octanol/ : Not applicable.

water (log Pow)

Vapor pressure : <0.01 kPa (<0.075006 mm Hg)

Density : 0.82 g/cm³ [15°C (59°F)] [ASTM D 4052]

: Not available.

Relative vapor density

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not applicable.

Oxidizing properties : Not applicable.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : Reactive or incompatible with the following materials:

Strong oxidizing materials

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name Resul

Severely refined mineral oil (C15 - C50) * - Rabbit - Dermal - LD50

H304 >5000 mg/kg

Rat - Oral - LD50 >5000 mg/kg

Rat - Male, Female - Inhalation - LC50 Dusts and mists

5.53 mg/l [4 hours] Acute Inhalation Toxicity

2,6-di-tert-butylphenol Rabbit - Dermal - LD50

>10 g/kg

Rat - Oral - LD50 1320 mg/kg

Distillates (petroleum), hydrotreated light

naphthenic

Rat - Oral - LD50

>5000 mg/kg

<u>Toxic effects</u>: Behavioral - Somnolence (general depressed

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 8/17

SECTION 11: Toxicological information

activity)

Rat - Inhalation - LC50 Dusts and mists

2180 mg/m³ [4 hours]

Toxic effects: Lung, Thorax, or Respiration - Structural or

functional change in trachea or bronchi

Conclusion/Summary [Product] : Not toxic.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/l)
Severely refined mineral oil (C15 - C50) * - H304	N/A	N/A	N/A	N/A	5.53

Skin corrosion/irritation

Product/ingredient name

Severely refined mineral oil (C15 - C50) * - H304

Result

Rabbit - Skin - Erythema/Eschar

Duration of treatment/exposure: 72 hours

Observation period: 7 days

Irritation score: 0.17

Fully reversible in 7 days or less

Rabbit - Skin - Edema

Duration of treatment/exposure: 72 hours

Observation period: 7 days

Irritation score: 0

Fully reversible in 7 days or less

2,6-di-tert-butylphenol Rat - Skin - Moderate irritant

Amount/concentration applied: 0.5 MI

Conclusion/Summary [Product]: Non-irritant to skin.

Serious eye damage/eye irritation

Product/ingredient name

Severely refined mineral oil (C15 - C50) * - H304

Result

Rabbit - Eyes - Iris lesion

Acute Eye Irritation/Corrosion

Duration of treatment/exposure: 48 hours

Observation period: 72 hours

Irritation score: 0

Fully reversible in 7 days or less

Rabbit - Eyes - Redness of the conjunctivae

Acute Eye Irritation/Corrosion

Duration of treatment/exposure: 48 hours

Observation period: 72 hours

Irritation score: 0.33

Fully reversible in 7 days or less

Conclusion/Summary [Product]: Non-irritating to the eyes.

Respiratory corrosion/irritation

Not available.

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 9/17

Result

Q8 Verdi 5

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Non-irritant to lungs.

Respiratory or skin sensitization

Product/ingredient name

Severely refined mineral oil (C15 - C50) * - Guinea pig - skin

H304 Skin Sensitization

Result: Not sensitizing

Skin

Conclusion/Summary [Product] : Not sensitizing

Respiratory

Conclusion/Summary [Product]: Not classified for respiratory sensitization.

Germ cell mutagenicity

Product/ingredient name Result

Severely refined mineral oil (C15 - C50) * - In vivo - Mammalian-Animal - Somatic - Intraperitoneal

H304 Mammalian Erythrocyte Micronucleus Test

Result: Negative

Conclusion/Summary [Product]: No mutagenic effect.

Carcinogenicity

Product/ingredient name Result

Severely refined mineral oil (C15 - C50) * - Mouse - Female - Dermal - TC

H304 Carcinogenicity Studies

78 weeks
Result: Negative

Conclusion/Summary [Product]: No carcinogenic effect.

Reproductive toxicity

Product/ingredient name Result

Severely refined mineral oil (C15 - C50) * - Rat - Male, Female - Oral

H304 Reproduction/Developmental Toxicity Screening Test

1000 mg/kg

Effects: No effect level.

Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Conclusion/Summary [Product]: No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name Result

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 10/17

Q8 Verdi 5

SECTION 11: Toxicological information

Severely refined mineral oil (C15 - C50) * -

ASPIRATION HAZARD - Category 1

H304

Distillates (petroleum), hydrotreated light

ASPIRATION HAZARD - Category 1

naphthenic

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion: Adverse symptoms may include the following:

nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -

H304

Result

Sub-chronic - Rat - Male, Female - Oral - NOAEL

Subchronic Dermal Toxicity: 90-day Study ≥2000 mg/kg [5 days per week] [13 weeks]

Sub-acute - Rat - Male - Oral - LOAEL

Repeated Dose 90-Day Oral Toxicity Study in Rodents

125 mg/kg [5 hours per day] [13 weeks]

Sub-acute - Rat - Male - Inhalation - NOAEL >980 mg/m³ [5 days per week] [4 weeks]

Conclusion/Summary [Product]: Not toxic.

General: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]: The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 11/17

Q8 Verdi 5

SECTION 11: Toxicological information

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

Severely refined mineral oil (C15 - C50) * - H304

Result

Acute - NEL - Fresh water

Fish, Acute Toxicity Test Fish - *Pimephales promelas* ≥100 mg/l [96 hours]

Acute - NEL - Fresh water

Daphnia sp. Acute Immobilization Test and Reproduction Test Daphnia - *Daphnia Magma* >10000 mg/l [48 hours]

Chronic - NEL - Fresh water

Daphnia Magna Reproduction Test Daphnia - *Daphnia magna* 10 mg/l [21 days] Effect: Reproduction

Acute - NEL - Fresh water

Alga, Growth Inhibition Test Algae >100 mg/l [72 hours] <u>Effect</u>: (growth rate)

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Severely refined mineral oil (C15 - C50) * - H304	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,6-di-tert-butylphenol	4.5	-	High

12.4 Mobility in soil

Soil/Water partition coefficient

Product/ingredient name	logKoc	Koc
2 ,6-di-tert-butylphenol	3.5	3181.17

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Severely refined mineral oil (C15 - C50) * - H304	No	No	No	No	No	No	No
2,6-di-tert-butylphenol	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light naphthenic	No	No	No	No	No	No	No

Mobility : Not available.

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 12/17

SECTION 12: Ecological information

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	В	T	vPvB	νP	vB
Severely refined mineral oil (C15 - C50) * - H304	No	No	No	No	No	No	No
2,6-di-tert-butylphenol	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light naphthenic	No	No	No	No	No	No	No

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB
Severely refined mineral oil (C15 - C50) * - H304	No						
2,6-di-tert-butylphenol Distillates (petroleum),	No No						
hydrotreated light naphthenic		110	110	110	110	110	110

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes. European waste catalogue (EWC)

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 13/17

Q8 Verdi 5

SECTION 13: Disposal considerations

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
፩ 8 Verdi 5	≥90	3

Labeling : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - : Not listed

Air

Date of issue/Date of revision : 08-04-2025 : 08-11-2022 Version: 1.06 Date of previous issue 14/17

Q8 Verdi 5

SECTION 15: Regulatory information

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants (1021/2019/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Germany

Hazard class for water : 1

(WGK)

Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.
Canada : Not determined.
China : Not determined.

Eurasian Economic Union : Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand Not determined. **Philippines** : Not determined. Republic of Korea : Not determined. **Taiwan** : Not determined. **Thailand** : Not determined. : Not determined. **Turkey United States of America** : Not determined. : Not determined. **Viet Nam**

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 15/17

SECTION 15: Regulatory information

15.2 Chemical Safety Assessment : Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: MDN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road

ASTM = American Society for Testing and Materials

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DIN = German Institute for Standardization
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EC = European Commission

EC50 = Half maximal effective concentration

EN = European Standard (Norm)

EUH statement = CLP-specific Hazard statement

GHS - Globally Harmonized System of Classification and Labeling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IC50 = Half maximal inhibitory concentration

IMDG = International Maritime Dangerous Goods

IMO = International Maritime Organisation

ISO = International Organization for Standardization

LC50 = Median lethal concentration

LD50 = Median lethal dose

LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration

NOEL / NOEC = No Observed Effect Level / Concentration

OECD = Organisation for Economic Co-operation and Development

OEL = Occupational Exposure Limit

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation (EC) No. 1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

SDS = Safety Data Sheet

SVHC = Substances of Very High Concern

STEL = Short Term Exposure Limit

TLV = Threshold Limit Value

TWA = Time Weighted Average

UFI = Unique Formula Identifier

UN = United Nations

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
,	Calculation method Calculation method

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 16/17

Q8 Verdi 5

SECTION 16: Other information

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

⊮ 304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2

Training advice: Ensure operatives are trained to minimise exposures.

Date of printing : 08-04-2025 Date of issue/ Date of : 08-04-2025

revision

Date of previous issue : 08-11-2022

Version : 1.06

Prepared by : Kuwait Petroleum Research & Technology B.V., The Netherlands

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 08-04-2025 Date of previous issue : 08-11-2022 Version : 1.06 17/17