

## Q8 Antifreeze Lobrid Evo PSI-OAT Premixed

Superior Long Life PSI-OAT Coolant

### Description

Q8 Antifreeze Lobrid Evo PSI-OAT Premixed is an ethylene glycol of the so-called PSI-OAT type and combines the advantages of phosphates and silicates and is based on so-called X-OAT technology. The product has unparalleled corrosion protection and Long Life properties. Does not contain amine, nitrite, boron or 2-ethylhexanoic acid compounds. Protects against cavitation and damage to the cylinder liner. Also suitable for aluminum engines.

### Applications

Q8 Antifreeze Lobrid Evo PSI-OAT Premixed is used in cooling systems for passenger cars, commercial vehicles, buses and stationary engines. This type of glycol is recommended mainly for the Volkswagen group but brands such as Volkswagen, Audi, Skoda, Porsche, Lamborghini, Bugatti but also fits other manufacturers.

### Benefits

- Excellent service life due to chemical stability.
- Outstanding high temperature performance.
- Outstanding compatibility with system rubber seals

### Specifications / Recommendations / Approvals

<b>AFNOR</b>	NF-R-15-601 1 except for RA	<b>JIS</b>	K2234:2018
<b>AS</b>	2108-2004	<b>Lamborghini</b>	VW TL 774 L
<b>ASTM</b>	D 3306	<b>MAN</b>	324 Type NF
<b>ASTM</b>	D 4985	<b>MAN</b>	324 Type Si-OAT
<b>ASTM</b>	D 6210 *	<b>MTU</b>	MTL 5048
<b>Audi</b>	VW TL 774 L	<b>MWM</b>	0199-99-2091/12
<b>BMW</b>	LC87, LC97, LC18	<b>Opel/Vauxhall</b>	GME L1301
<b>BS</b>	6580	<b>Porsche</b>	VW TL 774 L
<b>Bentley</b>	VW TL 774 L	<b>Scania</b>	*
<b>Bugatti</b>	VW TL 774 L	<b>Seat</b>	VW TL 774 L
<b>Cummins</b>	85T8-2	<b>Toyota</b>	1WW / 2WW Engine
<b>Daimler Truck AG</b>	DTFR 29C120 (MB 325.5)	<b>VAG</b>	VW TL 774 L (G12 EVO)
<b>Deutz</b>	DQC CC-14	<b>Volkswagen</b>	VW TL 774 L
<b>Fiat</b>	9.55523	<b>Volvo Cars</b>	128 6083
<b>Ford</b>	ESD-M97B49-A	<b>Volvo Cars</b>	TR-31854114-002
<b>GB</b>	29743.1 2014, 2022*	<b>Škoda</b>	VW TL 774 L
<b>Iveco</b>	18-1830		

\* Pending approval

### Properties

	Method	Unit	Typical
Colour	Visual	-	Pink
Density, 20 °C	D 4052	g/ml	1071
Refractive Index, 20 °C	D 1218	typ. Value	1.432
Boiling Point	-	°C	108
pH	D 1287	-	8.3
Freezing Protection	D 1177	°C	-36

The figures above are not a specification. They are typical figures obtained within production tolerances.