

## Q8 Bach XND 6

*Optimum performance neat metal removal fluid.*

### Description

Q8 Bach XND 6 is a chlorine free neat metal removal oil for multi-purpose, light to medium machining applications on non-ferrous metals like copper and aluminium. This product is formulated to optimize the performance and cost balance.

### Applications

Drilling and deep hole drilling of non-ferrous metals

### User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from water entry, frost and direct sunlight.

### Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.83
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	6
Flash Point, P-M	D 93	°C	140
Copper Strip, 3 h, 100 °C	D 130	-	1
Four Ball Test, Weld Load	IP 239	kg	250

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Bach XND 6 is **1.22** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**