

## Q8 Brahms 7006

Fluid for light duty forming and high speed punching

### Description

Q8 Brahms 7006 is the modern alternative to vanishing oils with a high flash point. It is a low viscosity, chlorine-free ferrous and non-ferrous forming oil with very good lubrication and evaporation properties.

### Applications

Q8 Brahms 7006 is recommended for light duty forming, high speed punching and general press work where minimal residues are required of ferrous and non-ferrous metals.

### User instructions

In order to preserve the integrity of this product, drums should be stored inside a building protected from frost and direct sunlight.

### Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

### Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	0.82
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	5
Flash Point, COC	D 92	°C	140
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Brahms 7006 is **1.25 kg CO<sub>2</sub>eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**