

Q8 Coolblu Premixed 50

Coolant for Passenger Cars and Commercial Vehicles

Description

Q8 Coolblu Premixed 50 is an outstanding concentrate that protects against freezing, boiling and corrosion of the cooling system. When mixed with water, the antifreeze forms a cooling liquid that transfers the heat from the combustion engine to the radiator. The long life of the Q8 Coolblu Premixed 50 is obtained by non-depleting corrosion inhibitors.

Applications

Q8 Coolblu Premixed 50 is used in cooling systems of all automotive passenger cars, commercial vehicles, busses and stationary internal combustion engines. It is also suited for most types industrial heat transfer and cooling systems.

Benefits

- Advanced long life protection against all forms of corrosion.
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime
- High and extended corrosion protection due to synergistic effects.
- Optimal cavitation corrosion prevention.
- Environmentally friendly corrosion inhibitor package.

Specifications, recommendations and approvals

AFNOR	NF R 15-601	SAE	J 1034
BS	6580	UNE	26-361-88/1
CUNA	NC 956-16	Önorm	V5123

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	1.184
Colour	Visual	-	Blue
Appearance (Emulsion)	Visual	-	Bright & Clear
Freezing Protection 33-67 %	D 1177	°C	-18
Freezing Protection 50-50 %	D 1177	°C	-34
Boiling Point	-	°C	105
pH	D 1287	-	9.3
Water content	D 1123	%	51.6

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Coolblu Premixed 50 is **1.20 kg CO₂eq / kg**.
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.
For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

