Demoulding oil



Q8 Dali 11

Demoulding oil for cement products

Description

Q8 Dali 11 is an exceptional demoulding oil for cement products. It is developed for tile manufacturing and forms a unique homogenous layer on the mould to provide a better quality of the surface. The light coloured Q8 Dali 11 makes it easy to inspect the quality of the moulds and doesn't smell. Extensive testing proves that the precise application quantities optimize costs and performance.

Applications

Q8 Dali 11 is used for tiles, white cement sheets, cement slates, fence posts and thin flat sections and other prefab elements of medium to higher quality.

Benefits

- Leads to an improved durability of the finished product quality
- Superior quality of the surface
- Neutral in odor
- Reliable and durable thanks to an effective demoulding operation
- Light colour
- Enriched with special additives
- Prevents sticking
- Extremely handy to apply
- Inherently biodegradable

Properties

	Method	Unit	Typical	
Appearance	Visual	-	Bright and Clear	
Kinematic Viscosity, 40 °C	D 445	mm²/s	11	
Pour Point	D 97	°C	-15	
Flash Point, COC	D 92	°C	174	
Rust Test, Proc. A and B, 24 h	D 665	-	pass	
Biodegradability, 28 days	OECD 301 B	%	inherent	

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Dali 11 is **1.24** kg CO_2 eq / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer. For more info check here

