

Q8 Dali 4

Light demoulding oil for cement products

Description

Q8 Dali 4 is a light demoulding oil for cement products. It is developed for tile manufacturing and forms a unique homogenous layer on the mould to provide a better quality of the surface. The light coloured Q8 Dali 4 makes it easy to inspect the quality of the moulds and doesn't smell. Extensive testing proves that the precise application quantities optimize costs and performance.

Applications

Q8 Dali 4 is used for tiles, white cement sheets, cement slates, fence posts and thin flat sections and other prefab elements of medium to higher quality.

Benefits

- Leads to an improved durability of the finished product quality
- Superior quality of the surface
- Neutral in odor
- Reliable and durable thanks to an effective demoulding operation
- Light colour
- Enriched with special additives
- Prevents sticking
- Extremely handy to apply

Properties

	Method	Unit	Typical
Appearance	Visual	-	bright & clear
Density, 15 °C	D 4052	g/ml	811
Kinematic Viscosity, 40 °C	D 445	mm ² /s	4.0
Flash Point, COC	D 92	°C	128
Rust Test, Proc. A and B, 24 h	D 665	-	pass

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Dali 4 is **1.22 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)

