

Q8 Formula Excel Long Life 0W-40

Full Synthetic ACEA A3/B4 passenger car engine oil

Description

Q8 Formula Excel Long Life 0W-40 is a full synthetic allround high SAPS high performance engine oil for passenger cars and light duty commercial vehicles. The lubricant guarantees advanced engine protection, and presents optimum cold weather starting properties. It is designed to counter sludge formation. It meets the ACEA A3/B4 specification.

Applications

Q8 Formula Excel Long Life 0W-40 is developed for passenger cars and vans with normally aspirated or turbocharged gasoline, LPG or (direct injection) diesel engines. It is especially recommended for high performance, multi-valve engines with catalyst. This versatile oil is an all season product that is suitable for different driving conditions.

Benefits

- Exceptional engine performance in different driving conditions.
- Exceptional engine protection after cold starting.
- Superior protection against rust and corrosion.
- Superior friction reduction.

Specifications, recommendations and approvals

ACEA	A3/B4	MB	229.5
API	SN	Porsche	A40
API	SP	Renault	RN 0700
BMW	Longlife-01	Renault	RN 0710
Chrysler	MS-10725	VAG	VW 502.00
Ford	M2C937-A	VAG	VW 505.00
MB	229.3	VAG	VW 505.01

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,847
Viscosity Grade	-	-	0W-40
Kinematic Viscosity, -40 °C	D 445	mm ² /s	81.9
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.1
Viscosity Index	D 2270	-	176
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=3.5
Pour Point	D 97	°C	-39
Flash Point, P-M	D 93	°C	221

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Excel Long Life 0W-40 is **1.88** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

