

Q8 Formula Exclusive C1 5W-30

Synthetic ACEA C1 passenger car engine oil

Description

Q8 Formula Exclusive C1 5W-30 is an exceptional performance passenger car engine oil, especially designed to provide superior engine durability, aftertreatment protection and fuel efficiency for Ford Euro 4 and 5 and Mazda Euro 4 passenger cars. It meets the specifications of industry organizations such as ACEA, and fulfills the requirements of OEMs such as Ford and Jaguar Land Rover.

Applications

Q8 Formula Exclusive C1 5W-30 is developed for Ford and Mazda cars with a Euro 4 diesel engine equipped with a DPF, and is suitable for passenger cars with normally aspirated or turbocharged gasoline, LPG or diesel Euro 4 and 5 engines, requiring low SAPS engine oil. It meets the Ford WSS M2C 934-B requirement.

Benefits

- Improved fuel economy.
- Superb protection for exhaust catalyst and diesel particulate filter.
- Outstanding engine protection after cold starting.
- Excellent protection against rust and corrosion.
- Excellent wear prevention ensuring long engine life.

Specifications, recommendations and approvals

ACEA	C1	Ford	M2C913-B
Ford	M2C912	Ford	M2C934-B
Ford	M2C913-A	Jaguar Land Rover	STJLR.03.5005

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,851
Viscosity Grade	-	-	SAE 5W-30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	57
Kinematic Viscosity, 100 °C	D 445	mm ² /s	10.2
Viscosity Index	D 2270	-	168
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=2.9
Apparent Viscosity, -30 °C	D 5293	mPa.s	4780
Pour Point	D 97	°C	-30
Flash Point, COC	D 92	°C	226

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Exclusive C1 5W-30 is **1.27** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

