

Q8 Formula Exclusive RN FE 0W-20

Ultra High Performance passenger car engines requiring Renault RN 17FE

Description

Q8 Formula Exclusive RN FE 0W-20 is a synthetic engine oil, offering exceptional fuel economy and extended drain intervals. This product provides superior protection against wear, rust and deposits. The low SAPS technology for Euro 6 exhausts offers ultimate protection for after treatment systems. Specially developed for reducing fuel consumption up to 3.0% Fuel Economy Improvement demonstrated in M111 FE engine test.

Applications

Specially developed for Renault Euro 6 passenger car engines requiring Renault RN 17FE

Benefits

- Exceptional fuel economy improvement of more than 3%.
- Exceptional engine performance in different driving conditions.
- Exceptional engine protection after cold starting.
- Extended drain interval capability
- Best-in-class wear prevention ensuring long engine life.

Specifications, recommendations and approvals

ACEA**C5****Renault****RN17 FE**

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,841
Viscosity Grade	-	-	SAE 0W-20
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.1
Kinematic Viscosity, 40 °C	D 445	mm ² /s	39.4
Viscosity Index	D 2270	-	187
Apparent Viscosity, -35 °C	D 5293	mPa.s	4600
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>2.6
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	204

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Exclusive RN FE 0W-20 is **1.46** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

