

Q8 Formula Exclusive V 0W-30

Synthetic VW 504.00/507.00 passenger car engine oil

Description

Q8 Formula Exclusive V 0W-30 is an exceptional performance, low SAPS engine oil, meeting the VW 504.00/507.00 and ACEA C3 standard. This product provides excellent protection against wear, enhanced durability and fuel economy.

Applications

Q8 Formula Exclusive V 0W-30 is designed for Euro 5 and 6 engines requiring VW 504.00/507.00, Porsche C30 and ACEA C3. It is developed for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 5 & Euro 6 engines requiring low SAPS engine oil.

Benefits

- Exceptional engine protection caused by stable viscosity during total service of the oil.
- Best-in-class wear prevention ensuring long engine life.
- Superior oxidation stability
- Superior protection for exhaust catalyst and diesel particulate filter.
- Fuel economy improvement of 1% or more

Specifications, recommendations and approvals

ACEA	C3	MB	Approval 229.51 *
BMW	Longlife-04	Porsche	C30
BMW	Longlife-12 FE	VAG	VW 504.00
BMW	Longlife-19 FE	VAG	VW 507.00
MB	229.52 *		

Color code blue = officially approved

* Pending approval

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0.840
Density, 15 °C	D 4052	g/ml	0,843
Viscosity Grade	-	-	0W-30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	61.3
Kinematic Viscosity, 100 °C	D 445	mm ² /s	12.4
Viscosity Index	D 2270	-	205
Flash Point, COC	D 92	°C	210
Pour Point	D 97	°C	-48
Sulfated Ash	D 874	% mass	0,78

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Exclusive V 0W-30 is **2.11** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

