

Q8 Formula Plus 15W-40

Mineral A3/B4 2021 passenger car engine oil

Description

Q8 Formula Plus 15W-40 is an advanced performance engine oil for passenger cars and light duty commercial vehicles. This lubricant ensures optimum engine protection, keeps the engine clean and prevents sludge formation. The product meets ACEA A3/B4 requirements.

Applications

Q8 Formula Plus 15W-40 is recommended for passenger cars and vans with gasoline or LPG engines. It is suitable for engines with a catalyst and normally aspirated as well as turbocharged diesel engines. The product meets ACEA A3/B4 2021 requirements.

Benefits

- Optimal wear prevention ensuring long engine life.
- High engine cleanliness increasing engine durability.
- Premium protection against rust and corrosion.

Specifications, recommendations and approvals

ACEA	A3/B4	MB	229.1
API	CF	VAG	VW 501.01
API	SN	VAG	VW 505.00

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0,863
Density, 15 °C	D 4052	g/ml	0,866
Kinematic Viscosity, 40 °C	D 445	mm ² /s	14.5
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	104
Viscosity Index	D 2270	-	144
Pour Point	D 97	°C	-27
Flash Point, COC	D 92	°C	220
Apparent Viscosity, -20 °C	D 5293	mPa.s	4300
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.