

## Q8 Formula R Long Life 5W-30

Synthetic ACEA C4 / RN 0720 passenger car engine oil

### Description

Q8 Formula R Long Life 5W-30 is a low SAPS engine oil for outstanding performance. This lubricant is suitable for passenger cars and light duty commercial vehicles. It is designed to provide excellent compatibility with aftertreatment systems, oxidation reduction by 20% and outstanding sludge formation prevention. It exceeds the requirements of ACEA C4.

### Applications

Q8 Formula R Long Life 5W-30 is developed for Renault, Nissan and Mitsubishi Euro 5 & 6 engines equipped with a DPF. This high-performance engine oil is especially recommended for Renault Euro 5 diesel DPF engines requiring RN 0720 engine oil specification. It exceeds the requirements of ACEA C4.

### Benefits

- Improved fuel economy.
- Excellent wear prevention ensuring long engine life.
- Superb protection for exhaust catalyst and diesel particulate filter.
- Outstanding engine cleanliness increasing engine durability.

### Specifications, recommendations and approvals

ACEA	C3	MB	229.31
ACEA	C4	MB	229.51
Fiat	9.55535-S4	Renault	RN 0720
MB	226.51		

Color code blue = officially approved

### Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	5W-30
Density, 20 °C	D 4052	g/ml	0,846
Density, 15 °C	D 4052	g/ml	0,849
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	67,4
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	11,8
Viscosity Index	D 2270	-	167
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	236

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula R Long Life 5W-30 is **1.18 kg CO<sub>2</sub>eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

