

Q8 Formula Techno FE 5W-30

Synthetic ACEA A5/B5 (Ford) passenger car engine oil

Description

Q8 Formula Techno FE 5W-30 is a passenger car engine oil for outstanding performance. It is also suitable for light duty commercial vehicles. This product provides fuel economy improvement up to 2,5% and outstanding protection against corrosion. It is designed for recent generation Ford Diesel and Gasoline engines meeting Euro 5 & Euro 6 emission legislation.

Applications

Q8 Formula Techno FE 5W-30 is designed for Ford engines, requiring specification WSS M2C 913-D, and is backwards compatible with all engines requiring Ford WSS M2C 912-A, 913-A/B & 913-C. It meets the requirements of ACEA A5/B5.

Specifications, recommendations and approvals

ACEA	A5/B5	Ford	M2C913-B
Fiat	9.55535-G1	Ford	M2C913-C
Ford	M2C912	Ford	M2C913-D
Ford	M2C913-A	Renault	RN 0700

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,85
Viscosity Grade	-	-	SAE 5W-30
Kinematic Viscosity, 40 °C	D 445	mm²/s	52.3
Kinematic Viscosity, 100 °C	D 445	mm²/s	9.7
Viscosity Index	D 2270	-	171
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	≥2.9
Apparent Viscosity, -30 °C	D 5293	mPa.s	4700
Pour Point	D 97	°C	-36
Flash Point, COC	D 92	°C	215

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Techno FE 5W-30 is **1.36 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF



VINÇOTTE