

Q8 Formula Truck 9000 FE 0W-20

Synthetic diesel engine oil for commercial vehicles

Description

Q8 Formula Truck 9000 FE 0W-20 is an superior ultra high performance low viscosity heavy-duty engine oil. This oil provides enhanced durability, reducing wear and corrosion, and is formulated to deliver superior fuel economy for modern generation heavy-duty diesel vehicles. This lubricant delivers fuel economy savings specially for Mercedes Trucks

Applications

Q8 Formula Truck 9000 FE 0W-20 is suitable for use for all Euro VI vehicles fitted with latest generation after-treatment devices such DPFs and SCRs where use of Mercedes Trucks

Benefits

- Extended drain interval capability
- Best-in-class engine cleanliness.
- Fuel economy improving technology
- Superior engine cleanliness increasing engine durability.
- Superior Bio-diesel compatibility due to improved oxidation stability.

Specifications, recommendations and approvals

Daimler Truck AG DTFR 15C140 (MB 228.71)

Properties

	Method	Unit	Typical
Viscosity Grade	-	-	SAE OW-20
Density, 15 °C	D 4052	g/ml	0,847
Kinematic Viscosity, 40 °C	D 445	mm²/s	38.6
Kinematic Viscosity, 100 °C	D 445	mm²/s	7.4
Flash Point, P-M	D 93	°C	222
Pour Point	D 97	°C	-45
Total Base Number	D 2896	mg KOH/g	9
Sulfated Ash	D 874	% mass	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Formula Truck 9000 FE 0W-20 is **1.46** kg CO_2 eq / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer. For more info check here



