

Q8 Formula Truck 9000 FE 5W-20

Synthetic diesel engine oil for commercial vehicles

Description

Q8 Formula Truck 9000 FE 5W-20 is an superior ultra high performance low viscosity heavy-duty engine oil. This oil provides enhanced durability, reducing wear and corrosion, and is formulated to deliver superior fuel economy for modern generation heavy-duty diesel vehicles. This lubricant delivers fuel economy savings specially for MAN and SCANIA

Applications

Q8 Formula Truck 9000 FE 5W-20 is suitable for use for all Euro VI vehicles fitted with latest generation after-treatment devices such DPFs and SCR's where use of MAN M3977 or SCANIA LDF-5 is requested

Benefits

- Extended drain interval capability
- Best-in-class engine cleanliness.
- Fuel economy improving technology
- Superior engine cleanliness increasing engine durability.
- Superior Bio-diesel compatibility due to improved oxidation stability.

Specifications / Recommendations / Approvals

MAN**M 3977****Scania****LDF-5**

Color code blue = officially approved

Properties

	Method	Unit	Typical
Viscosity Grade	-	-	SAE 5W-20
Density, 15 °C	D 4052	g/ml	0,856
Kinematic Viscosity, 40 °C	D 445	mm ² /s	46.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.1
Borderline Pumping Temperature	D 3829	°C	-36
Flash Point, P-M	D 93	°C	196
Pour Point	D 97	°C	-42
Total Base Number	D 2896	mg KOH/g	13
Sulfated Ash	D 874	% mass	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Truck 9000 FE 5W-20 is **1.46** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

