

Q8 Formula Ultra V R 0W-20

Synthetic Volvo VCC RBS0-2AE passenger car engine oil

Description

Q8 Formula Ultra V R 0W-20 is a superior low SAPS passenger car engine oil for Volvo Euro 6 engines. This lubricant offers 3,4% fuel saving according to the M 111 fuel economy test, extends oil drain intervals and provides ultimate protection against wear, rust and deposits. The low SAPS technology for Euro 6 exhausts provides best-in-class protection for aftertreatment system

Applications

Q8 Formula Ultra V R 0W-20 is especially developed for Volvo Euro 6 passenger car engines requiring Volvo VCC RBS0-2AE

Benefits

- Exceptional fuel economy improvement up to 3.4%.
- Exceptional engine protection after cold starting.
- Superior protection for SCR catalyst and diesel particulate filter.
- Extended drain interval capability
- Superior viscosity index providing strong lubricant film at all operating conditions.

Specifications, recommendations and approvals

API	SN	Volvo	VCC RBS0-2AE
-----	----	-------	--------------

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,845
ISO Viscosity Grade	-	-	0W-20
Kinematic Viscosity, 40 °C	D 445	mm ² /s	48.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.0
Viscosity Index	D 2270	-	173
Apparent Viscosity, -35 °C	D 5293	mPa.s	5700
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	204
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=2.6

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Ultra V R 0W-20 is **2.11 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

