

Q8 Formula V Blue 0W-20

Full synthetic VW 508.00/509.00 and Porsche C20 passenger car engine oil

Description

Q8 Formula V Blue 0W-20 is a best-in-class full synthetic engine oil, offering exceptional fuel economy and extended drain intervals. This product provides superior protection against wear, rust and deposits. The low SAPS technology for Euro 6 exhausts offers ultimate protection for aftertreatment systems. It meets VW 508.00/509.00 and Porsche C20 specifications.

Applications

Q8 Formula V Blue 0W-20 is developed for VW Euro 6 engines requiring the VW 508.00/509.00 specification and Porsche C20.

Benefits

- Improved fuel economy.
- Exceptional engine performance in different driving conditions.
- Exceptional engine protection after cold starting.
- Extended drain interval capability
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

ACEA	C5	VAG	VW 508.00
Ford	M2C956-A1	VAG	VW 509.00
Porsche	C20		

Color code blue = officially approved

Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	0W-20
Density, 15 °C	D 4052	g/ml	0,833
Density, 20 °C	D 4052	g/ml	0,830
Kinematic Viscosity, 40 °C	D 445	mm²/s	39,0
Kinematic Viscosity, 100 °C	D 445	mm²/s	8,0
Viscosity Index	D 2270	-	179
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=2.6 <2.9
Apparent Viscosity, -35 °C	D 5293	mPa.s	3200
Pour Point	D 97	°C	-57
Flash Point, COC	D 92	°C	220

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula V Blue 0W-20 is **1.42** kg CO_2 eq / kg.

Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer. For more info check here



www.Q80ils.com

PRODUCT CARBON FOOTPRINT METHOD VALIDATED BY: PCF CALCULATION IN LINE WITH: ISO 14067 | ATIEL-UEIL PCF

