

Q8 Garden Pro Synt 4T 5W-30

Superior garden oil

Description

Q8 Garden Pro Synt 4T 5W-30 is a superior synthetic multigrade lubricant for garden equipment. It guarantees an exceptional performance in both air and water cooled engines. Q8 Garden Pro Synt 4T 5W-30 has been enriched with unique components that improve lubricity and enhance detergency and cleanliness. The reliable garden oil offers an extreme wear protection.

Applications

Q8 Garden Pro Synt 4T 5W-30 is used in all 4-stroke gasoline engines of garden equipment such as lawn mowers, rider mowers and snow blowers. It is a reliable lubricant that covers a broad range of applications and can be used in the most severe conditions.

Specifications, recommendations and approvals

API

CF

API

SL

Properties

| | Method | Unit | Typical |
|-----------------------------|----------|--------------------|---------|
| Density, 15 °C | D 4052 | g/ml | 0,851 |
| Viscosity Grade | - | - | 5W-30 |
| Kinematic Viscosity, 40 °C | ISO 3104 | mm ² /s | 64.3 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 11.3 |
| Viscosity Index | D 2270 | - | 169 |
| Apparent Viscosity, -30 °C | D 5293 | mPa.s | 4300 |
| Flash Point, P-M | D 93 | °C | 237 |
| Pour Point | D 97 | °C | -36 |
| Sulfated Ash | D 874 | % mass | 1.2 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Garden Pro Synt 4T 5W-30 is **1.34** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

