

Q8 Gear Oil V LD 75W-90

Full synthetic long drain transmission fluid for Volvo, Daimler Truck, MAN and ZF

Description

Q8 Gear Oil V LD 75W-90 is a superior full synthetic transmission fluid providing excellent lubrication in high load transmissions. This product offers class-leading thermal stability and fuel saving properties. Meets the API GL-4 specification and developed to meet Volvo 97315, Volvo 97319 and MB 235.11

Applications

Q8 Gear Oil V LD 75W-90 is especially designed for heavy duty transmissions requiring MB 235.11. The lubricant can also be recommended for all vehicles that require a 75W-90 viscosity oil and when the API GL-4 or MAN 341 Z4/E3, ZF 02L and Volvo 97315/97319 specifications are prescribed by the manufacturer

Benefits

- Full synthetic formulation to provide an extreme thermal stability.
- Outstanding protection against wear and extends component life.
- Outstanding protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.
- Superior gear protection under heavy duty conditions.

Specifications, recommendations and approvals

API	GL-4	Renault	
DAF		Volvo	97315 (400.000 km)
Eaton/Fuller	Europe Extended drain (300.000 km)	Volvo	97319 (800.000 km)
Iveco		ZF	TE-ML 01L
MAN	341 Type E3	ZF	TE-ML 02L
MAN	341 Type Z4	ZF	TE-ML 08
MB	235.11 (DTFR 13B110)	ZF	TE-ML 16K
MB	235.4		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,868
Viscosity Grade	-	-	75W-90
Kinematic Viscosity, 40 °C	D 445	mm ² /s	119
Kinematic Viscosity, 100 °C	D 445	mm ² /s	17.8
Viscosity Index	D 2270	-	165
Brookfield Viscosity, -40 °C	D 2983	Pa.s	55
Flash Point, P-M	D 93	°C	221
Pour Point	D 97	°C	-42

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Gear Oil V LD 75W-90 is **1.21** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

