

Q8 Haydn 10

Advanced zinc-based hydraulic oil

Description

Q8 Haydn 10 oil consists of a zinc-based additive technology. This oil can be used in all sorts of operational applications and industrial equipment. Q8 Haydn 10 oil has an optimum thermal and oxidation stability and has a long service life time.

Applications

Q8 Haydn 10 is suitable for all kinds of systems, general industrial hydraulic applications and other industrial applications (low charged gears, pumps, compressors, bearings). Q8 Haydn 10 is also applied in pneumatics (spindle oil and bearing applications) and in central machine lubrication (not in gears, pumps, compressors).

Benefits

- Limited products needed thanks to versatile applications of lubricants
- Highly fit for different operations
- Outstanding oxidation stability
- Advanced performance against wear

Specifications & Approvals

AFNOR	NF E 48-603 HM	Eaton Brochure	03-401-2010
Bosch Rexroth	RE 90220 notes	ISO	11158 HM
DIN	51524-2 HLP	ISO	19378 FD 10

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	10
Colour	D 1500	-	0,5
Density, 15 °C	D 4052	g/ml	0,864
Density, 20 °C	D 4052	g/ml	0,842
Kinematic Viscosity, 40 °C	D 445	mm ² /s	10
Kinematic Viscosity, 100 °C	D 445	mm ² /s	2,7
Viscosity Index	D 2270	-	100
Pour Point	D 97	°C	-33
Flash Point, COC	D 92	°C	165
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(5)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	50/30/50
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Haydn 10 is **1.23** kg CO₂eq / kg.*

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**