

Q8 Mahler C 15W-40

High performance gas engine oil

Description

Q8 Mahler C is high performance gas engine oil for engines requiring Cummins CES 20074 specification. The product is suitable for four stroke gas engines operating under normal or heavy duty conditions.

Applications

Four stroke gas engines operating under normal or heavy duty conditions.

Features

Enhanced technology

Benefits

Excellent low temperature and fluidity performance, providing outstanding protection at low temperatures and cold-start conditions

Extended drain

Excellent alkalinity reserve maintains engine performance and durability while extending oil drain interval

Engine performance

Outstanding resistance against pre-ignition and knocking

Specifications & Approvals

Cummins

CES 20074

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,884
Viscosity Grade	-	-	SAE 15W-40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	106.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.1
Viscosity Index	D 2270	-	135
Total Base Number	D 2896	mg KOH/g	5
Pour Point	D 97	°C	-24
Flash Point, P-M	D 93	°C	190
Sulfated Ash	D 874	% mass	0.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

The original manufacturers recommendation should be followed

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Mahler C 15W-40 is **1.31 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**