

## Q8 Mahler G1 SAE 30

High performance two-stroke gas engine oil

### Description

Q8 Mahler G1 is recommended for two-stroke gas engines where low ash or ashless oils are recommended. Q8 Mahler G1 can also be used to lubricate reciprocating compressors in which natural gas is compressed and pressures do not exceed 10.000 kPa. Using Q8 Mahler G1 in both the gas engine and the gas compressor will simplify the lubricant inventory.

### Applications

Two-stroke gas engines where low ash or ashless oils are recommended.

#### Features

##### Enhanced technology

#### Benefits

Maximizes oil life due to exceptional oxidative and thermal stability even at high temperatures

Exceptional lubricity properties providing low wear of engine components, significantly reducing maintenance costs

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,88
Appearance	Visual	-	Bright and Clear
Viscosity Grade	-	-	SAE 30
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	88,3
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	11,0
Viscosity Index	D 2270	-	110
Total Base Number	D 2896	mg KOH/g	2,8
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	220

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

The original manufacturers recommendation regarding the selection of the ash level should always be followed

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Mahler G1 SAE 30 is **1.30** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we  
take  
care**