

Q8 T 2300 CVT 15W-40

Exceptional synthetic Tractor Continuous Variable Transmission Fluid

Description

Q8 T 2300 CVT 15W-40 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 T 2300 CVT 15W-40 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

Applications

Q8 T 2300 CVT 15W-40 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant.

Benefits

- Excellent viscosity retention providing smoothless CVT operation.
- Superb oxidation stability.
- Outstanding frictional properties for smooth brake operation.
- Excellent response of hydraulic components.
- Superb compatibility with conventional elastomers.

Specifications, recommendations and approvals

AGCO	CVT ML 200	Valtra	G2-B10 (XT-60+)
API	GL-4	ZF	TE-ML 03E
Case New Holland	MAT 3505	ZF	TE-ML 05F
Case New Holland	MAT 3506	ZF	TE-ML 06B
Case New Holland	MAT 3525	ZF	TE-ML 06B
Case New Holland	MAT 3540	ZF	TE-ML 06D
Caterpillar	SATO	ZF	TE-ML 06E
Claas	CVT	ZF	TE-ML 06F
Fendt	FWN 81001	ZF	TE-ML 06K
Fendt	Vario	ZF	TE-ML 06L
John Deere	JDM J20C	ZF	TE-ML 06M
Komatsu	KES 07.866	ZF	TE-ML 06N
Kubota	UDT	ZF	TE-ML 06P
Massey Ferguson	CMS M 1145	ZF	TE-ML 06R
New Holland	NH 410-B	ZF	TE-ML 06S
New Holland	NH 410-C	ZF	TE-ML 06T
Same Deutz Fahr		ZF	TE-ML 17E
Valtra	G2-08 (XT-60)	ZF	TE-ML 21F

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,872
Viscosity Grade	SAE J306	SAE	75W-90
Viscosity Grade	SAE J300	SAE	15W-40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	97.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.1
Viscosity Index	D 2270	-	148
Brookfield Viscosity, -26 °C	D 2983	mPa.s	6
Pour Point	D 97	°C	-33
Flash Point, P-M	D 93	°C	208

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 2300 CVT 15W-40 is **1.33** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

