

Q8 T 35 SAE 140

API GL-4 manual transmission fluid

Description

Q8 T 35 SAE 140 is an advanced manual transmission fluid. It is developed for synchromesh transmissions, offering optimal low temperature fluidity and protection under high pressure. It meets the requirements of the API GL-4 specification.

Applications

Q8 T 35 SAE 140 is formulated for synchromesh transmissions. It meets the requirements of the API GL-4 specification.

Benefits

- Outstanding protection against wear and extends component life.
- Outstanding protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.
- Stay-in grade shear stability

Specifications, recommendations and approvals

API	GL-4	MB	235.1 (DTFR 13B100)
-----	------	----	---------------------

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,906
Viscosity Grade	-	-	SAE 140
Kinematic Viscosity, 40 °C	D 445	mm ² /s	347
Kinematic Viscosity, 100 °C	D 445	mm ² /s	25.4
Viscosity Index	D 2270	-	96
Pour Point	D 97	°C	-15
Flash Point, P-M	D 93	°C	>200

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 35 SAE 140 is **1.25** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

