

Q8 T 520 SAE 10W

Mineral API CG-4 heavy-duty engine oil

Description

Q8 T 520 SAE 10W is a heavy-duty engine oil formulated to suit the needs of old generation vehicles with turbocharged engines. The oil has been formulated with a special package of additives and detergents/dispersants. It provides advanced anti-wear capacity, optimum lubrication and keeps the engine clean.

Applications

Q8 T 520 SAE 10W can be used as engine or transmission lubricant in commercial vehicles, buses, off-highway/construction or military equipment. It's developed for old generation vehicles having turbocharged engines. To be used where monograde engine oil is preferred

Benefits

- High protection against rust and corrosion.
- Premium protection against engine wear.

Specifications, recommendations and approvals

API	CG-4	ZF	TE-ML 03B
NATO	O-237		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.879
Viscosity Grade	-	-	SAE 10W
Kinematic Viscosity, 40 °C	D 445	mm ² /s	45.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7.3
Viscosity Index	D 2270	-	121
Total Base Number	D 2896	mg KOH/g	8.5
Pour Point	D 97	°C	-30
Flash Point, P-M	D 93	°C	210
Sulfated Ash	D 874	% mass	1.1

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Can also be used as HLPD 32 hydraulic oil

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 520 SAE 10W is **1.34 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

