

## Q8 T 750 SAE 30

Heavy-duty engine oil ACEA E7 and API CI-4.

### Description

Q8 T 750 SAE 30 is an advanced heavy-duty engine oil. It provides good lubrication, limits wear, prohibits corrosion and protects against rust.

### Applications

Q8 T 750 SAE 30 can be used as diesel engine or transmission lubricant in commercial vehicles, buses, off-highway/construction and military equipment. It's developed for engines normally aspirated, turbocharged or supercharged, with or without intercooling and Tier 3 engine technology. To be used where monograde engine oil is preferred

### Benefits

- Premium protection against engine wear.
- High protection against rust and corrosion.
- Advanced engine protection after cold start.

### Specifications, recommendations and approvals

ACEA	A3/B4	MAN	M 270
ACEA	E3	MB	227.0
ACEA	E5	MB	228.0
ACEA	E7	MTU	Type 1
API	CI-4	MTU	Type 2
API	SL	Voith	Retarder
Caterpillar	TO-2		

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,889
Viscosity Grade	-	-	SAE 30
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	90.5
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	11.2
Viscosity Index	D 2270	-	109
Total Base Number	D 2896	mg KOH/g	10
Pour Point	D 97	°C	-27
Flash Point, P-M	D 93	°C	206
Sulfated Ash	D 874	% mass	1.3

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 750 SAE 30 is **1.33** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

