

Q8 T 750 SAE 50

Mineral API CI-4 and ACEA E7 heavy duty engine oil

Description

Q8 T 750 SAE 50W is a heavy duty engine oil. This product is designed to improve engine durability and to prevent deposit formation. It prevents corrosion and foaming. It meets the requirements of API CI-4 ACEA E7.

Applications

Q8 T 750 SAE 50W for commercial vehicles, buses, off-highway/construction or military equipment. To be used where monograde engine oil is preferred in some transmission applications.

Benefits

- Premium protection against engine wear.
- High protection against rust and corrosion.
- Advanced engine protection after cold start.

Specifications, recommendations and approvals

ACEA	A3/B4	API	CI-4
ACEA	E3	API	SL
ACEA	E5	MTU	Type 1
ACEA	E7		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,893
Viscosity Grade	-	-	SAE 50
Kinematic Viscosity, 40 °C	D 445	mm ² /s	200
Kinematic Viscosity, 100 °C	D 445	mm ² /s	18.0
Viscosity Index	D 2270	-	103
Total Base Number	D 2896	mg KOH/g	10
Pour Point	D 97	°C	-24
Flash Point, P-M	D 93	°C	204
Sulfated Ash	D 874	% mass	1.3

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 750 SAE 50 is **1.33** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

