

## Q8 T 800 10W-30

Synthetic based API CI-4 and ACEA E7 heavy-duty engine oil

### Description

Q8 T 800 10W-30 is a super high performance heavy-duty engine oil which offers optimum engine durability and prevents deposit formation. This lubricant provides advanced protection against bore polishing and cam and cylinder wear, reduces maintenance costs and prevents corrosion and foaming.

### Applications

Q8 T 800 10W-30 is designed for normally aspirated, turbocharged or supercharged engines, with or without intercooling. It is recommended for most heavy-duty diesel engines for on- and off highway applications. It meets the ACEA E7 and API CI-4 specification as well as the requirements of MAN, MB, Volvo, Caterpillar, Cummins and MTU. Can also be used for Passenger Cars requiring API SL.

### Benefits

- Premium protection against engine wear.
- Advanced engine protection after cold start.
- High protection against piston rings deposits.
- High protection against rust and corrosion.

### Specifications, recommendations and approvals

ACEA	E7	Cummins	CES 20077
API	CI-4	Cummins	CES 20078
API	SL	MAN	M 3275-1
Caterpillar	ECF-1a	MB	228.3 (DTFR 15B110)
Caterpillar	ECF-2	Mack	EO-M Plus
Cummins	CES 20071	Renault	RLD
Cummins	CES 20072	Renault	RLD-2
Cummins	CES 20076	Volvo	VDS-2

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,875
Viscosity Grade	-	-	SAE 10W-30
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	75
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	11.3
Viscosity Index	D 2270	-	146
Total Base Number	D 2896	mg KOH/g	10
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	220
Sulfated Ash	D 874	% mass	1.3
Borderline Pumping Temperature	D 3829	°C	-42

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 800 10W-30 is **1.39** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

