

## Q8 Terra 4000 UTTO CVT 75W-85

Exceptional Synthetic Tractor Continuous Variable Transmission Fluid

### Description

Q8 Terra 4000 UTTO CVT 75W-85 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 T Q8 Terra 4000 UTTO CVT 75W-85 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

### Applications

Q8 Terra 4000 UTTO CVT 75W-85 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant. The oil meets the requirements of almost all OEMs.

### Benefits

- Superior viscosity retention providing smoothless CVT operation.
- Best-in-class oxidation stability.
- Superior frictional properties for smooth brake operation.
- Superior response of hydraulic components.
- Maximum compatibility with conventional elastomers.

### Specifications, recommendations and approvals

AGCO	CVT ML 200	Same Deutz Fahr	UTTO
API	GL-4	Valtra	G2-08 (XT-60)
Case	MS 1207 / MS 1209	Valtra	G2-B10 (XT-60+)
Case	MS 1210	ZF	TE-ML 03E / 03G / 03L
Case New Holland	MAT 3505	ZF	TE-ML 05F
Case New Holland	MAT 3525 / MAT 3540	ZF	TE-ML 06B
Case New Holland	MAT 3541 / MAT 3544	ZF	TE-ML 06D
Case New Holland	MAT 3552-A / MAT 3553-A	ZF	TE-ML 06E
Caterpillar	SATO	ZF	TE-ML 06F
Claas	CVT	ZF	TE-ML 06K
Deutz	Allis AC Power Fluid 821 XL	ZF	TE-ML 06L
Fendt	FWN 81001	ZF	TE-ML 06M
Fendt	Vario	ZF	TE-ML 06N
John Deere	JDM J20C	ZF	TE-ML 06P
Komatsu	KES 07.866	ZF	TE-ML 06R
Kubota	UDT / Super UDT / UDT-HD	ZF	TE-ML 06S
Massey Ferguson	CMS M 1135	ZF	TE-ML 06T
Massey Ferguson	CMS M 1141 / M 1143 / M 1145	ZF	TE-ML 17E
New Holland	NH 410-B / NH 410-C	ZF	TE-ML 21F

## Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	10W-30
Viscosity Grade	SAE J306	SAE	75W-85
Density, 15 °C	D 4052	g/ml	0,861
Density, 20 °C	D 4052	g/ml	0,858
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	71.1
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	12.0
Viscosity Index	D 2270	-	166
Brookfield Viscosity, -20 °C	D 2983	mPa.s	3400
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	240

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Terra 4000 UTTO CVT 75W-85 is **1.30** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

