

Q8 Unishift PC Synt 75W-90

Synthetic API GL-4 manual transmission fluid

Description

Q8 Unishift PC Synt 75W-90 is a superior manual transmission fluid for passenger cars and light duty vehicles. This versatile lubricant offers exceptional protection and durability, even under extreme pressure, and provides best-in-class thermal stability, making it suitable for a wide variety of passenger car applications. It meets the requirements of most OEMs based on API GL-4.

Applications

Q8 Unishift PC Synt 75W-90 is a versatile lubricant designed to be used in passenger cars and light duty synchromesh manual gearboxes and transaxles, specifically in high load carrying situations. It meets the API GL-4 specification and the requirements of most European and Asian manufacturers.

Benefits

- Exceptional low temperature fluidity and wide temperature operating range.
- Exceptional internal friction reduction.
- Excellent easy gear shifting at low temperatures.
- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

API	GL-4	Nissan	
Alfa Romeo		PSA	B71 2330
BMW/MINI	MTF-LT4	Toyota	
Fiat	9.55550-MX3	VAG	VW 501.50
Fiat	9.55550-MZ1	VAG	VW G 005 000
Fiat	9.55550-MZ3	VAG	VW G 005 100
Fiat	9.55550-MZ4	VAG	VW G 052 145
Ford	M2C200-C	VAG	VW G 052 157
GM	1940768	VAG	VW G 052 190
GM	B 040 104 3	VAG	VW G 052 911
GM	B 040 104 3	VAG	VW G 50
Honda	MTF 94	VAG	VW G 51
Honda	MTF II/SG	Volvo	97308
Honda	Special MTF	Volvo	97309
MB	235.10	Volvo	97310
Mitsubishi			

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,868
Viscosity Grade	-	-	SAE 75W-90
Kinematic Viscosity, 40 °C	D 445	mm ² /s	87
Kinematic Viscosity, 100 °C	D 445	mm ² /s	15.6
Viscosity Index	D 2270	-	191
Brookfield Viscosity, -40 °C	D 2983	Pa.s	25
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	196

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Unishift PC Synt 75W-90 is **1.56** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

