

## Q8 Formula Prestige V 5W-30

Ultra High Performance Low SAPS, ACEA C3, API SP and VW 504.00/507.00 Baumuster test engine oil.

### Description

Q8 Formula Prestige V 5W-30 is a Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 5 & 6 engines. This product passed the latest VW 504.00/507.00 Baumuster test, MB 229.52 and BMW Longlife-04 (B48) tests. The product furthermore offers protection against Low Speed Pre-Ignition (LSPI)

### Applications

Q8 Formula Prestige V 5W-30 is a Synthetic Engine Oil for Euro 5 & 6 engines for VW, Mercedes, Porsche and BMW and all cars requiring an ACEA C3, API SN, SN Plus, SP and cars using Gasoline or Diesel Particulate Filter (GPF or DPF)

### Benefits

- LSPI (Low Speed Pre Ignition) compatible formulation for turbocharged gasoline engines
- Superior protection for exhaust catalyst and diesel particulate filter.
- Exceptional engine protection caused by stable viscosity during total service of the oil.
- Exceptional fuel economy improvement up to 2% or more.

### Specifications, recommendations and approvals

ACEA	C3	PSA	B71 2297
ACEA	Recommended for ACEA C2	Porsche	<b>C30</b>
API	SP	Renault	RN 0700
BMW	<b>Longlife-04 (B48)</b>	Renault	RN 0710
BMW	Longlife-19 FE	VAG	VW 501.01
Chrysler	MS-11106	VAG	VW 502.00
Fiat	9.55535-S1	VAG	VW 503.00
GM	Dexos2	VAG	VW 503.01
MB	229.31	VAG	<b>VW 504.00 Baumuster 2020</b>
MB	<b>229.51</b>	VAG	VW 505.00
MB	<b>229.52</b>	VAG	VW 505.01
Opel/Vauxhall	OV0401547-D30 *	VAG	VW 506.00
Opel/Vauxhall	OV0401547-G30 *	VAG	VW 506.01
PSA	B71 2290	VAG	<b>VW 507.00 Baumuster 2020</b>

Color code blue = officially approved

\* Pending approval

### Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	5W-30
Density, 15 °C	D 4052	g/ml	0,852
Density, 20 °C	D 4052	g/ml	0,849
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	69,1
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	12,1
Viscosity Index	D 2270	-	174
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	3,7
Apparent Viscosity, -30 °C	D 5293	mPa.s	5600
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	234

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Prestige V 5W-30 is **1.26** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

