

Q8 T 650 10W-40

Synthetic based ACEA A3/B4 passenger car engine oil

Description

Q8 T 650 10W-40 is an allround high SAPS advanced performance engine oil for passengers cars and light duty commercial vehicles. This product guarantees improved engine protection by providing a strong lubricating film in different operating conditions and meets the requirements of ACEA A3/B4

Applications

Q8 T 650 10W-40 is developed for Euro 3 and 4 engines used in the majority of car manufacturers. It is designed for passenger cars and vans with gasoline or LPG engines, and is suited for normally aspirated or turbocharged diesel engines with or without direct injection.

Benefits

- Advanced engine protection after cold starting.
- High engine performance in different driving conditions.
- Premium protection against rust and corrosion.

Specifications, recommendations and approvals

ACEA	A3/B4	MB	229.1
API	CF	VAG	VW 505.00
API	SL		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,874
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	14.5
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	98.4
Viscosity Index	D 2270	-	152
Apparent Viscosity, -25 °C	D 5293	mPa.s	6410
Borderline Pumping Temperature	D 3829	°C	-30.2
Pour Point	D 97	°C	-30
Flash Point, P-M	D 93	°C	202

The figures above are not a specification. They are typical figures obtained within production tolerances.