SAFETY DATA SHEET

Q8 Gear Oil V LD 75W-90



| SECTION 1: Identific undertaking | on of the substance/mixture and of the company/ | | |
|--|---|-------|--|
| 1.1 Product identifier | | | |
| Product name | Q8 Gear Oil V LD 75W-90 | | |
| Viscosity or Type | SAE 75W-90 | | |
| 1.2 Relevant identified uses | e substance or mixture and uses advised against | | |
| Material uses | Lubricating oil for automotive transmissions | | |
| 1.3 Details of the supplier of | safety data sheet | | |
| Supplier | Q8Oils Italia S.r.I. Via Volpedo 2 15050 Castellar Guidobono (AL) Tel. +39 02-90595.1, Fax +39 02-90076347 e-mail: Q8OilsItalia@Q8.it | | |
| Manufacturer / Distributor | Q8Oils Italia S.r.l./Kuwait Petroleum Belgium N.V.Via Volpedo 2Petroleumkaai 715050 Castellar Guidobono (AL)B-2020 AntwerpItalyBelgium | /S.A. | |
| e-mail address of person responsible for this SDS | SDSinfo@Q8.com, communication preferably in English only. | | |
| PCN Information contact | PCNinfo@Q8.com, communication preferably in English only. | | |
| 1.4 Emergency telephone nu | r | | |
| Italy | 800 699 792 (Toll free) CARECHEM24 | | |
| Europe | +44 (0) 1235 239 670 | | |
| Global (English only) | +44 (0) 1865 407 333 | | |
| National advisory body/Po | Center | | |
| Italy | CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA (ROMA) : 06 68593726 Az. Osp. Univ. Foggia (FOGGIA) : 800183459 Az. Osp. "A. Cardarelli" (NAPOLI) : 081-5453333 CAV Policlinico "Umberto I" (ROMA) : 06-49978000 CAV Policlinico "A. Gemelli" (ROMA) : 06-3054343 Az. Osp. "Careggi" U.O. Tossicologia Medica (FIRENZE) : 055-7947819 CAV Centro Nazionale di Informazione Tossicologica (PAVIA) : 0382-24444 Osp. Niguarda Ca' Granda (MILANO) : 02-66101029 Azienda Ospedaliera Papa Giovanni XXII (BERGAMO) : 800883300 Azienda Ospedaliera Integrata Verona (VERONA) : 800011858 | | |

SECTION 2: Hazards identification

| 2.1 | Classification | of | the | substance | or | mixture |
|-----|----------------|----|-----|-----------|----|---------|
|-----|----------------|----|-----|-----------|----|---------|

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown : None. toxicity

Q8 Gear Oil V LD 75W-90

SECTION 2: Hazards identification

Ingredients of unknown

not result in classification

ecotoxicity

: None.

See Section 11 for more detailed information on health effects and symptoms.

| 2.2 Label elements | | |
|---|------------|--|
| Signal word | : | No signal word. |
| Hazard statements | 1 | No known significant effects or critical hazards. |
| Precautionary statements | | |
| Prevention | : | Not applicable. |
| Response | : | Not applicable. |
| Storage | : | Not applicable. |
| Disposal | : | Not applicable. |
| Supplemental label elements | : | Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction. Safety data sheet available on request. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Not applicable. |
| Special packaging requirem | <u>ier</u> | <u>its</u> |
| Containers to be fitted with child-resistant fastenings | : | Not applicable. |
| Tactile warning of danger | : | Not applicable. |
| 2.3 Other hazards | | |
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do | 1 | Prolonged or repeated contact may dry skin and cause irritation. |

SECTION 3: Composition/information on ingredients

| 3.2 Mixtures | : Mixture | | | | |
|---|---|-----------------|---|--|---------|
| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
| Severely refined mineral oil (C15 - C50) * - H304 | - | ≤5 | Asp. Tox. 1, H304 | - | [1] [2] |
| Reaction products of bis (4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | REACH #: 01-2119493620-38 EC: 931-384-6 | <2.5 | Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411 | ATE [Oral] = 2000 mg/kg Eye Irrit. 2, H319: C ≥ 50% Skin Sens. 1, H317: C ≥ 9.39% | [1] |
| Date of issue/Date of revision | : 18-07-2025 Da | ate of previous | issue : 07-01-2025 | Version : 1.0 | 2 2/ |

Q8 Gear Oil V LD 75W-90

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

* Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25 CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29 CAS: 64742-56-9, EC: 265-159-2, EU REACH: 01-2119480132-48 CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

| Eye contact | : | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|----------------------------|---|--|
| Inhalation | : | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : | Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : | Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

4.2 Most important symptoms and effects, both acute and delayed

| Over-exposure signs/symptoms | | | | |
|------------------------------|--|--|--|--|
| Eye contact | : No specific data. | | | |
| Inhalation | : No specific data. | | | |
| Skin contact | : Adverse symptoms may include the following: irritation dryness cracking | | | |
| Ingestion | : No specific data. | | | |

4.3 Indication of any immediate medical attention and special treatment needed

|--|

3/16

Q8 Gear Oil V LD 75W-90

| SECTION 4: First aid | I measures |
|---|---|
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |
| SECTION 5: Firefigh | ting measures |
| 5.1 Extinguishing media | |
| Suitable extinguishing media | : Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog). |
| Unsuitable extinguishing media | : Do not use water jet. |
| 5.2 Special hazards arising | rom the substance or mixture |
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous combustion products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides |
| 5.3 Advice for firefighters | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, pro | te | ctive equipment and emergency procedures |
|--------------------------------|-----|---|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| 6.3 Methods and materials fo | r c | ontainment and cleaning up |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. |

Q8 Gear Oil V LD 75W-90

SECTION 6: Accidental release measures

| 6.4 | Reference | to | other |
|-----|-----------|----|-------|
| sec | tions | | |

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

| Protective measures Advice on general occupational hygiene | Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on bygiene measures. |
|--|--|
| | information on hygiene measures. |

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations: Not available.Industrial sector specific: Not available.solutions: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| H304 | EU OEL (Europe) TWA 8 hours: 5 mg/m³. Form: Mist. STEL 15 minutes: 10 mg/m³. Form: Mist. |

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Not available.

PNECs

Q8 Gear Oil V LD 75W-90

SECTION 8: Exposure controls/personal protection

Not available.

| 8.2 Exposure controls | | |
|-------------------------------------|------|--|
| Appropriate engineering controls | : | Good general ventilation should be sufficient to control worker exposure to airborne contaminants. |
| Individual protection meas | ures | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. |
| Skin protection | | |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes. |
| Body protection | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : | Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2. Gas and combination filter cartridges should comply with the European standard EN14387. |
| Environmental exposure controls | : | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

| Appearance | | |
|---|-------------------------------------|-------------|
| Physical state | : Liquid. [Oily liquid.] | |
| Appearance | : Not available. | |
| Color | : Brownish | |
| Odor | : Not available. | |
| Odor threshold | : Not available. | |
| Melting point/freezing point | : Not applicable. | |
| Pour point | : -57°C (-70.6°F) [ASTM D 97] | |
| Boiling point or initial boiling point and boiling range | : Not available. | |
| Flammability | : Not available. | |
| Date of issue/Date of revision | : 18-07-2025 Date of previous issue | :07-01-2025 |

Q8 Gear Oil V LD 75W-90

| SECTION 9: Physical and chemical properties | | | |
|---|---|--|--|
| Lower and upper explosion limit | : Not available. | | |
| Flash point | : Closed cup: >110°C (>230°F) | | |
| Auto-ignition temperature | : >200°C (>392°F) | | |
| Decomposition temperature | : Not available. | | |
| рН | : Not applicable. | | |
| Viscosity | Kinematic (40°C (104°F)): 61.5 mm²/s (61.5 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 10.1 mm²/s (10.1 cSt) [ASTM D 445] | | |
| Solubility | 1 · · · · · · · · · · · · · · · · · · · | | |
| Natavallahla | | | |

Not available.

| Partition coefficient n-octanol/ | 1 | Not applicable. |
|----------------------------------|---|-----------------|
| water (log Pow) | | |

Vapor pressure

: Not available.

| | V | apor Pressi | ure at 20°C | N | Vapor pressure at 50°C | | |
|-------------------------------|--------|---------------|-----------------|---------|------------------------|----------|--|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | | |
| bis (nonylphenyl)amine | <0.01 | <0.0013 | EU A.4 | 0.0019 | 0.00025 | Fretifod | |
| Density | : 0.85 | 5 g/cm³ [15°(| C (59°F)] [ASTM | D 4052] | | | |
| Relative vapor density | : Not | available. | | | | | |
| Particle characteristics | | | | | | | |
| Median particle size | : Not | applicable. | | | | | |

9.2 Other information

| 9.2.1 Information with regard to physical haza | ard classes |
|--|-------------|
|--|-------------|

- **Explosive properties**
- : Not available.
- **Oxidizing properties** : Not available.
- 9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

| 10.1 Reactivity | : | No specific test data related to reactivity available for this product or its ingredients. |
|--|---|--|
| 10.2 Chemical stability | : | The product is stable. |
| 10.3 Possibility of hazardous reactions | : | Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : | No specific data. |
| 10.5 Incompatible materials | : | No specific data. |
| 10.6 Hazardous decomposition products | : | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Q8 Gear Oil V LD 75W-90

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -H304

Result

Rabbit - Dermal - LD50 >5000 mg/kg

Rat - Oral - LD50 >5000 mg/kg

Rat - Male, Female - Inhalation - LC50 Dusts and mists 5.53 mg/l [4 hours] Acute Inhalation Toxicity

Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Rat - Male, Female - Oral - LD50 2000 mg/kg OECD 401

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|-------------------------|-------------------|--------------------------------|----------------------------------|--|
| Q8 Gear Oil V LD 75W-90 Severely refined mineral oil (C15 - C50) * - H304 Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | 156257.6 N/A 2000 | N/A N/A N/A | N/A N/A N/A | N/A N/A N/A | N/A 5.53 N/A |

Skin corrosion/irritation

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -H304

Result

Rabbit - Skin - Erythema/Eschar

<u>Duration of treatment/exposure</u>: 72 hours <u>Observation period</u>: 7 days <u>Irritation score</u>: 0.17 Fully reversible in 7 days or less

Rabbit - Skin - Edema

<u>Duration of treatment/exposure</u>: 72 hours <u>Observation period</u>: 7 days <u>Irritation score</u>: 0 Fully reversible in 7 days or less

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -H304

Result

Rabbit - Eyes - Iris lesion

Acute Eye Irritation/Corrosion <u>Duration of treatment/exposure</u>: 48 hours <u>Observation period</u>: 72 hours <u>Irritation score</u>: 0 Fully reversible in 7 days or less

Q8 Gear Oil V LD 75W-90

SECTION 11: Toxicological information

| SECTION II. TOXICOlogical informati | |
|--|---|
| | Rabbit - Eyes - Redness of the conjunctivaeAcute Eye Irritation/CorrosionDuration of treatment/exposure: 48 hoursObservation period: 72 hoursIrritation score: 0.33Fully reversible in 7 days or less |
| Conclusion/Summary [Product] : Not available | 9. |
| Respiratory corrosion/irritation Not available. | |
| Conclusion/Summary [Product] : Not available | Э. |
| Respiratory or skin sensitization Product/ingredient name Severely refined mineral oil (C15 - C50) * - H304 | Result Guinea pig - skin Skin Sensitization <u>Result</u> : Not sensitizing |
| Skin Conclusion/Summary [Product] : Not available | Э. |
| Respiratory Conclusion/Summary [Product] : Not available | θ. |
| Germ cell mutagenicity | |
| Product/ingredient name | Result |
| Severely refined mineral oil (C15 - C50) * - H304 | In vivo - Mammalian-Animal - Somatic - Intraperitoneal Mammalian Erythrocyte Micronucleus Test <u>Result</u> : Negative |
| Conclusion/Summary [Product] : Not available | 9. |
| Carcinogenicity | |
| Product/ingredient name Severely refined mineral oil (C15 - C50) * - H304 | Result Mouse - Female - Dermal - TC Carcinogenicity Studies 78 weeks Result: Negative |
| Conclusion/Summary [Product] : Not available | Э. |
| Reproductive toxicity | |
| Product/ingredient name Severely refined mineral oil (C15 - C50) * - H304 | Result Rat - Male, Female - Oral Reproduction/Developmental Toxicity Screening Test 1000 mg/kg <u>Effects</u> : No effect level. <u>Maternal toxicity</u> : Negative <u>Fertility effects</u> : Negative Developmental: Negative |

Conclusion/Summary [Product] : Not available.

Developmental: Negative

Q8 Gear Oil V LD 75W-90

SECTION 11: Toxicological information

Specific target organ toxicity (single exposure) Not available. Specific target organ toxicity (repeated exposure) Not available. Aspiration hazard **Product/ingredient name** Result Severely refined mineral oil (C15 - C50) * -**ASPIRATION HAZARD - Category 1** H304 Information on the likely routes of exposure Not available. Potential acute health effects Eve contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : Defatting to the skin. May cause skin dryness and irritation. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics : No specific data. Eye contact Inhalation : No specific data. **Skin contact** : Adverse symptoms may include the following: irritation dryness cracking Ingestion : No specific data. Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure **Potential immediate** : Not available. effects **Potential delayed effects** : Not available. Long term exposure **Potential immediate** : Not available. effects **Potential delayed effects** : Not available. Potential chronic health effects **Product/ingredient name** Result Severely refined mineral oil (C15 - C50) * -Sub-chronic - Rat - Male, Female - Oral - NOAEL H304 Subchronic Dermal Toxicity: 90-day Study ≥2000 mg/kg [5 days per week] [13 weeks] Sub-acute - Rat - Male - Oral - LOAEL Repeated Dose 90-Day Oral Toxicity Study in Rodents 125 mg/kg [5 hours per day] [13 weeks] Sub-acute - Rat - Male - Inhalation - NOAEL >980 mg/m³ [5 days per week] [4 weeks] Conclusion/Summary [Product] : Not available. General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis. Carcinogenicity : No known significant effects or critical hazards. **Mutagenicity** : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Date of issue/Date of revision

: 18-07-2025 Date of previous issue

of previous issue : 07-01-2025

10/16

Q8 Gear Oil V LD 75W-90

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -H304

Result

Acute - NEL - Fresh water Fish, Acute Toxicity Test Fish - *Pimephales promelas* ≥100 mg/l [96 hours]

Acute - NEL - Fresh water

Daphnia sp. Acute Immobilization Test and Reproduction Test Daphnia - *Daphnia Magma* >10000 mg/l [48 hours]

Chronic - NEL - Fresh water

Daphnia Magna Reproduction Test Daphnia - *Daphnia magna* 10 mg/l [21 days] Effect: Reproduction

Acute - NEL - Fresh water

Alga, Growth Inhibition Test Algae >100 mg/l [72 hours] <u>Effect</u>: (growth rate)

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Severely refined mineral oil (C15 - C50) * - H304 | - | - | Inherent |

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/Water partition coefficient Not available.

Results of PMT and vPvM assessment

Q8 Gear Oil V LD 75W-90

SECTION 12: Ecological information

| Product/ingredient name | PMT | Р | Μ | т | vPvM | vP | ٧M |
|--|-----|----|----|----|------|----|----|
| Severely refined mineral oil (C15 - C50) * - H304 | No | No | No | No | No | No | No |
| Reaction products of bis (4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | No | No | No | No | No | No | No |

Mobility Conclusion/Summary : Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

| Product/ingredient name | PBT | Р | В | Т | vPvB | vP | vB |
|--|-----|----|----|----|------|----|----|
| Severely refined mineral oil (C15 - C50) * - H304 | No | No | No | No | No | No | No |
| Reaction products of bis (4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | No | No | No | No | No | No | No |

Regulation (EC) No. 1272/2008 [CLP]

| Product/ingredient name | PBT | Р | В | т | vPvB | vP | vB |
|--|-----|----|----|----|------|----|----|
| Severely refined mineral oil (C15 - C50) * - H304 | No | No | No | No | No | No | No |
| Reaction products of bis (4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) | No | No | No | No | No | No | No |
| Conclusion/Summary : The product does not meet the criteria to be considered as a PBT or vPvB. Regulation (EC) No. 1272/2008 | | | | | | | |

[CLP]

12.6 Endocrine disrupting properties

```
Conclusion/Summary [Product]
```

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Q8 Gear Oil V LD 75W-90

SECTION 13: Disposal considerations

| Methods of disposal | : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
|---------------------|---|
| Hazardous waste | : Yes. |

European waste catalogue (EWC)

| Waste code | Waste designation |
|---------------------|---|
| 13 02 05* | mineral-based non-chlorinated engine, gear and lubricating oils |
| Packaging | |
| Methods of disposal | : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
| Special precautions | : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |

SECTION 14: Transport information

| | - | | | | | |
|------------------------------------|----------------|----------------|----------------|----------------|--|--|
| | ADR/RID | ADN | IMDG | ΙΑΤΑ | | |
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | | |
| 14.2 UN proper shipping name | - | - | - | - | | |
| 14.3 Transport hazard class(es) | - | - | - | - | | |
| 14.4 Packing group | - | - | - | - | | |
| 14.5 Environmental hazards | No. | No. | No. | No. | | |

14.6 Special precautions for: Transportuserupright and

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Q8 Gear Oil V LD 75W-90 SECTION 15: Regulatory information Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles No listed substance **Other EU regulations** Industrial emissions : Not listed (integrated pollution prevention and control) -Air **Industrial emissions** : Not listed (integrated pollution prevention and control) -Water : Not applicable. **Explosive precursors** Ozone depleting substances (EU 2024/590) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants (1021/2019/EU) Not listed. **Seveso Directive** This product is not controlled under the Seveso Directive. **National regulations** Germany Hazard class for water : 1 (WGK) Italy D.Lgs. 152/06 : Not determined. D.Lgs. 81/2008 : Health and Safety in the workplace. D.Lgs. 25/2002 : Protection against risks from chemical agents. D.Lgs. 65/2003 : Classification Labelling and Packaging of Dangerous Products. D.M. 14/01/2008 : List of work related deseases that require notification. Switzerland **VOC content** : Exempt. International regulations **Chemical Weapon Convention List Schedules I, II & III Chemicals** Not listed. **Montreal Protocol** Not listed. **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

| Inventory I | ist |
|-------------|-----|
|-------------|-----|

| Australia | : All components are listed or exempted. | |
|-----------|--|--|
| Canada | : All components are listed or exempted. | |

Date of issue/Date of revision

Q8 Gear Oil V LD 75W-90

SECTION 15: Regulatory information

| China | 1 | All components are listed or exempted. |
|--------------------------|---|---|
| Eurasian Economic Union | : | Russian Federation inventory: Not determined. |
| Japan | : | Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined. |
| New Zealand | : | All components are listed or exempted. |
| Philippines | : | All components are listed or exempted. |
| Republic of Korea | 1 | Not determined. |
| Taiwan | 1 | Not determined. |
| Thailand | 1 | Not determined. |
| Turkey | 1 | Not determined. |
| United States of America | 1 | All components are active or exempted. |
| Viet Nam | 1 | Not determined. |
| 15.2 Chemical Safety | : | This product contains substances for which Chemical Safety Assessments are still |

Assessment

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version

| Abbreviations and | at has changed from previously issued version. : ADN = European Provisions concerning the International Carriage of Dangerous |
|--------------------------------|--|
| acronyms | Goods by Inland Waterway |
| us.onymo | ADR = The European Agreement concerning the International Carriage of |
| | Dangerous Goods by Road |
| | ASTM = American Society for Testing and Materials |
| | ATE = Acute Toxicity Estimate |
| | BCF = Bioconcentration Factor |
| | CAS = Chemical Abstracts Service |
| | CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] |
| | DIN = German Institute for Standardization |
| | DMEL = Derived Minimal Effect Level |
| | DNEL = Derived No Effect Level |
| | EC = European Commission |
| | EC50 = Half maximal effective concentration |
| | EN = European Standard (Norm) |
| | EUH statement = CLP-specific Hazard statement |
| | GHS - Globally Harmonized System of Classification and Labeling of Chemicals |
| | IATA = International Air Transport Association |
| | IBC = Intermediate Bulk Container |
| | IC50 = Half maximal inhibitory concentration |
| | IMDG = International Maritime Dangerous Goods |
| | IMO = International Maritime Organisation |
| | ISO = International Organization for Standardization |
| | LC50 = Median lethal concentration |
| | LD50 = Median lethal dose |
| | LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration |
| | MARPOL = International Convention for the Prevention of Pollution From Ships, |
| | 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) |
| | N/A = Not available |
| | NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration |
| | NOEL / NOEC = No Observed Effect Level / Concentration |
| | OECD = Organisation for Economic Co-operation and Development |
| | OEL = Occupational Exposure Limit |
| | PBT = Persistent, Bioaccumulative and Toxic |
| | PNEC = Predicted No Effect Concentration |
| | REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals |
| | Regulation [Regulation (EC) No. 1907/2006] |
| | RID = The Regulations concerning the International Carriage of Dangerous Goods |
| | by Rail |
| Date of issue/Date of revision | : 18-07-2025 Date of previous issue : 07-01-2025 Version : 1.02 15/ |

Q8 Gear Oil V LD 75W-90

SECTION 16: Other information

| SDS = Safety Data Sheet |
|---|
| SVHC = Substances of Very High Concern |
| STEL = Short Term Exposure Limit |
| TLV = Threshold Limit Value |
| TWA = Time Weighted Average |
| UFI = Unique Formula Identifier |
| UN = United Nations |
| VOC = Volatile Organic Compound |
| vPvB = Very Persistent and Very Bioaccumulative |
| |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

| H302 H304 H317 | Harmful if swallowed. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. |
|----------------------|--|
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Full text of classifications [CLP/GHS]

| Acute Tox. 4 Aquatic Chronic 2 Asp. Tox. 1 Eye Irrit. 2 Skin Sens. 1B | ACUTE TOXICITY - Category 4 AQUATIC HAZARD (LONG-TERM) - Category 2 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SKIN SENSITIZATION - Category 1B |
|---|---|
| | |
| Training advice | : Ensure operatives are trained to minimise exposures. |
| Date of printing | : 18-07-2025 |
| Date of issue/ Date of revision | : 18-07-2025 |
| Date of previous issue | e : 07-01-2025 |
| Version | : 1.02 |
| Prepared by | : Kuwait Petroleum Research & Technology B.V., The Netherlands |
| | |

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.