

## Q8 Formula Truck 9000 FE 0W-20

Synthetic diesel engine oil for commercial vehicles

### Description

Q8 Formula Truck 9000 FE 0W-20 is an superior ultra high performance low viscosity heavy-duty engine oil. This oil provides enhanced durability, reducing wear and corrosion, and is formulated to deliver superior fuel economy for modern generation heavy-duty diesel vehicles. This lubricant delivers fuel economy savings specially for Mercedes Trucks

### Applications

Q8 Formula Truck 9000 FE 0W-20 is suitable for use for all Euro VI vehicles fitted with latest generation after-treatment devices such DPFs and SCR's where use of Mercedes Trucks

### Benefits

- Extended drain interval capability
- Best-in-class engine cleanliness.
- Fuel economy improving technology
- Superior engine cleanliness increasing engine durability.
- Superior Bio-diesel compatibility due to improved oxidation stability.

### Specifications, recommendations and approvals

Daimler Truck AG

DTFR 15C140 (MB 228.71)

Iveco

18-1804 TLV LS

### Properties

	Method	Unit	Typical
Viscosity Grade	-	-	SAE 0W-20
Density, 15 °C	D 4052	g/ml	0,847
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	38.6
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	7.4
Flash Point, P-M	D 93	°C	222
Pour Point	D 97	°C	-45
Total Base Number	D 2896	mg KOH/g	9
Sulfated Ash	D 874	% mass	1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Truck 9000 FE 0W-20 is **1.46** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

