

Q8 Dusart BIO 3.5

Exceptional anti-sticking fluid for the paper industry

Description

Q8 Dusart Bio 3.5 is an exceptional anti-sticking fluid for the paper industry. This superior colour free fluid extends the maintenance intervals of the drying cylinders, reduces production downtime and limits production losses. Q8 Dusart Bio 3.5 prevents paper web breakage, is easy applicable by spraying or mixing and is solvent free.

Applications

Q8 Dusart Bio 3.5 is used in drying cylinders in the paper industry. It creates an anti-sticking layer to prevent the web from sticking and is easily applied by spraying or mixing into the pulp. Q8 Dusart Bio 3.5 is also used as an anti-sticking oil for asphalt plants, asphalt trucks and for cleaning tools at the work site.

Benefits

- Minimizes downtime which leads to a higher maintenance efficiency
- Prevents sticking
- Avoids paper breakage
- Limited impact on the environment
- Solvent free
- Readily biodegradable
- High flash point
- Light colour

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.819
Colour	D 1500	-	L 0.5
Kinematic Viscosity, 40 °C	D 445	mm ² /s	3.6
Pour Point	D 97	°C	-21
Flash Point, COC	D 92	°C	132
Biodegradability, 28 days	OECD 301 B	%	61

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Dusart BIO 3.5 is **1.21 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

