

Q8 Dynobear 3

Excellent multi-purpose circulating oil

Description

Q8 Dynobear 3 is an excellent multi-purpose lubricant developed for machine-tool spindle bearings. It contains a certain additive to reduce friction and eliminate stick-slip and judder that might occur in spindle bearings. Q8 Dynobear 3 has a long service life, outstanding corrosion protection, excellent anti-wear characteristics and high chemical and thermal stability.

Applications

Q8 Dynobear 3 is used for spindle bearings in machinery that is subject to high speeds and fine clearances such as grinders, jig borers and lathes.

Benefits

- Decreased downtime thanks to increased maintenance efficiency
- Limited products needed thanks to versatile applications of lubricants
- Excellent decrease of friction
- Prevents sticking
- Excellently fit for different operations

Specifications & Approvals

DIN	51517-2 CL	ISO	6743-2 F
-----	------------	-----	----------

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	3
Density, 15 °C	D 4052	g/ml	0,814
Kinematic Viscosity, 40 °C	D 445	mm ² /s	3.476
Kinematic Viscosity, 100 °C	D 445	mm ² /s	1.33
Viscosity Index	D 2270	-	100
Flash Point, COC	D 92	°C	144
Colour	D 1500	-	L 1.0

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Dynobear 3 is **1.48 kg CO₂eq / kg**.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

