

## Q8 El Greco 320

Excellent synthetic industrial gear oil based on PAO-technology

### Description

Q8 El Greco 320 is an excellent synthetic industrial gear oil based on the Poly-Alpha-Olefin (PAO) technology. This technology leads to an increased energy saving and a maximal friction reduction. The composition of the Q8 El Greco 320 results in an outstanding performance in the grey staining test and guarantees a long lubricant lifetime.

### Applications

Q8 El Greco 320 is perfect for use in heavily industrial gearboxes operating in rough conditions such as wind turbines, paper and steel mills, cement and mining, plastic extrusion and injection, aerators and agitators and chemical process industry.

### Benefits

- Extends service life time thus minimal costs and maximal efficiency
- Enhanced efficiency of operations, equipment and machines
- Exceptional anti-wear characteristics
- Highly appropriate for applications under heavy conditions
- Outstanding oxidation stability
- Excellently recommended in a wide range of temperatures
- Excellent synthetic oil
- Excellent friction reduction

### Specifications & Approvals

ANSI/AGMA  
DIN

9005-E02 6 EP  
51517-3 CLP-HC

ISO  
Siemens Flender

12925-1 CKC-CKD

### Properties

|                                   | Method    | Unit               | Typical  |
|-----------------------------------|-----------|--------------------|----------|
| ISO Viscosity Grade               | -         | -                  | 320      |
| Colour                            | D 1500    | -                  | 4,5      |
| Density, 20 °C                    | D 4052    | g/ml               | 0,860    |
| Density, 15 °C                    | D 4052    | g/ml               | 0,866    |
| Kinematic Viscosity, 40 °C        | D 445     | mm <sup>2</sup> /s | 320      |
| Kinematic Viscosity, 100 °C       | D 445     | mm <sup>2</sup> /s | 32,1     |
| Viscosity Index                   | D 2270    | -                  | 140      |
| Pour Point                        | D 97      | °C                 | -24      |
| Flash Point, COC                  | D 92      | °C                 | 238      |
| Foam, 5 min blowing, seq. 1-2-3   | D 892     | ml                 | 10/20/10 |
| Foam, 10 min settling, seq. 1-2-3 | D 892     | ml                 | 0/0/0    |
| Copper Strip, 3 h, 100 °C         | D 130     | -                  | 1        |
| Rust Test, Proc. A and B, 24 h    | D 665     | -                  | pass     |
| Colour                            | D 1500    | -                  | 1        |
| FZG Test, A/8.3/90                | DIN 51354 | load stage         | >14      |
| FZG Test, A/16.6/90               | DIN 51354 | load stage         | >12      |
| FZG Test, A/16.6/140              | DIN 51354 | load stage         | >12      |
| FZG Grey Staining Test, 60 °C     | FVA 54-7  | load stage         | >10      |

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Miscible and compatible with mineral and PAO-based gear oils.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 El Greco 320 is **1.85** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

