

Q8 Formula Techno Eco FE 0W-20

Synthetic ACEA C6 and Ford WSS M2C-952A1 passenger car engine oil

Description

Q8 Formula Techno Eco FE 0W-20 is a synthetic, superior performance passenger car engine oil. Low in SAPS, this lubricant protects the aftertreatment systems and offers exceptional wear protection, engine cleanliness and fuel consumption reduction. It is biofuel compatible and is especially developed for the latest Ford cars requiring Ford WSS-M2C-952A1.

Applications

Q8 Formula Techno Eco FE 0W-20 is designed for the latest Ford engines requiring Ford WSS-M2C-952A1 and ACEA C6. This lubricant is also recommended for Fiat, Landrover and Jaguar.

Benefits

- Exceptional engine protection caused by stable viscosity during total service of the oil.
- Exceptional fuel economy improvement of more than 3%.
- Extended drain interval capability
- LSPI (Low Speed Pre Ignition) compatible formulation for turbocharged gasoline engines
- Best-in-class wear prevention ensuring long engine life.

Specifications, recommendations and approvals

ACEA	C5	GM	Dexos D (OV0401547)
ACEA	C6	Jaguar Land Rover	STJLR.03.5006
API	SN Plus	Jaguar Land Rover	STJLR.51.5122
API	SN Plus-RC	MB	229.71
API	SP	Opel/Vauxhall	OV0401547 (Dexos D)
API	SP-RC	Opel/Vauxhall	OV0401547-A20
Ford	M2C952-A1 *	VAG	VWC 53037
Ford	M2C954-A1 *		

Color code blue = officially approved

* Pending approval

Properties

	Method	Unit	Typical
Viscosity Grade	SAE J300	SAE	0W-20
Kinematic Viscosity, 40 °C	D 445	mm ² /s	41
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.3
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=2.6 <2.9
Apparent Viscosity, -35 °C	D 5293	mPa.s	5100
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	205
Density, 15 °C	D 4052	g/ml	0.843
Density, 20 °C	D 4052	g/ml	0.840

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Techno Eco FE 0W-20 is **1.37** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

