

## Q8 Hindemith 15

Exceptional zinc-free hydraulic oil

### Description

Q8 Hindemith 15 oil is a zinc-free exceptional lubricant used in the roughest and coldest conditions. Its extreme high viscosity index leads to excellent flow properties in all temperatures and applications. The Q8 Hindemith 15 has superior cold start abilities so it is the perfect solution for major OEM's in stringent conditions.

### Applications

Q8 Hindemith 15 is developed for major OEM's working in severe conditions. Perfect for mining, off-road, forestry,... all types of applications operating in an extremely wide temperature range .

### Benefits

- Can be used in all seasons and a wide range of temperatures
- Extensive oil drain interval for a longer lubricant lifetime
- Exceptionally high viscosity index
- Superior flow properties
- Long term stable fluid viscosity through excellent shear stability
- Extremely suitable for applications in a broad temperature spectrum
- Exceptional reduction of oil oxidation
- Easy start ability performance at very low temperatures

### Specifications & Approvals

**DIN** 51524-3 HVLP **ISO** 11158 HV

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	15
Density, 15 °C	D 4052	g/ml	0,875
Colour	D 1500	-	L 0.5
Kinematic Viscosity, -20 °C	D 445	mm <sup>2</sup> /s	105
Kinematic Viscosity, -30 °C	D 445	mm <sup>2</sup> /s	169
Kinematic Viscosity, -40 °C	D 445	mm <sup>2</sup> /s	317
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	15.0
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	5.59
Viscosity Index	D 2270	-	375
Total Acid Number	D 974	mg KOH/g	0.30
Pour Point	D 97	°C	-51
Flash Point, COC	D 92	°C	100
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(5)
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1
Oxidation stability, Time to 2.0 TAN	D 943	hrs	7800
FZG Test, A/8.3/90	DIN 51354	load stage	pass 10

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Hindemith 15 is **1.21** kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



**we  
take  
care**

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

