

SAFETY DATA SHEET

Q8 Auto 15 S



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Q8 Auto 15 S
Product description : Hydraulic fluids

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Lubricating oil for automotive transmissions

1.3 Details of the supplier of the safety data sheet

Supplier : Kuwait Petroleum Companies in the Benelux
Company Office: Desguinlei 100 - 8, 2018 Antwerp, Belgium
Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium
Tel. +32 3 247 38 11, Fax +32 3 216 03 42

Manufacturer / Distributor : Kuwait Petroleum Belgium N.V./S.A. / Q8Oils Italia S.r.l.
Petroleumkaai 7 Via Volpedo 2
B-2020 Antwerp 15050 Castellar Guidobono (AL)
Belgium Italy

e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only.

PCN Information contact : PCNinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Europe : +44 (0) 1235 239 670
Global (English only) : +44 (0) 1865 407 333



National advisory body/Poison Center

Belgium : Poison Centre : +32 (0)70 245 245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

AQUATIC HAZARD (LONG-TERM) Category 3 H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : None.

Ingredients of unknown ecotoxicity : None.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.
Hazard statements : H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements

Q8 Auto 15 S

SECTION 2: Hazards identification

General	: P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	: P273 - Avoid release to the environment.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8	≤3	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≤3	Not classified.	-	[2]
2,6-di-tert-butylphenol	REACH #: 01-2119490822-33 EC: 204-884-0 CAS: 128-39-2	<1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	Skin Irrit. 2, H315: C ≥ 35% M [Acute] = 1 M [Chronic] = 1	[1]

Q8 Auto 15 S

SECTION 3: Composition/information on ingredients

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	REACH #: 01-2119510877-33 EC: 620-540-6 CAS: 1218787-32-6	≤0.3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 10 M [Chronic] = 1	[1]
3-((C9-11-iso,C10-rich) alkyloxy) propan-1-amine	REACH #: 01-2119974116-35 EC: 939-485-7 CAS: 218141-16-3	<0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 100 M [Chronic] = 1	[1]
naphthalene	EC: 202-049-5 CAS: 91-20-3 Index: 601-052-00-2	<0.1	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 490 mg/kg M [Acute] = 1 M [Chronic] = 1	[1] [2]

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
sulfur oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

SECTION 6: Accidental release measures

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Q8 Auto 15 S

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
Distillates (petroleum), hydrotreated light paraffinic	Limit values (Belgium, 12/2023) [Olie] TWA 8 hours: 5 mg/m ³ . Form: mist. STEL 15 minutes: 10 mg/m ³ . Form: mist. EU OEL (Europe) TWA 8 hours: 5 mg/m ³ . STEL 15 minutes: 10 mg/m ³ .
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Limit values (Belgium, 12/2023) [Olie] TWA 8 hours: 5 mg/m ³ . Form: mist. STEL 15 minutes: 10 mg/m ³ . Form: mist. EU OEL (Europe) TWA: 5 mg/m ³ (oil Mist).
Distillates (petroleum), hydrotreated heavy paraffinic	Limit values (Belgium, 12/2023) [Olie] TWA 8 hours: 5 mg/m ³ . Form: mist. STEL 15 minutes: 10 mg/m ³ . Form: mist. EU OEL (Europe) TWA: 5 mg/m ³ .
Distillates (petroleum), solvent-refined heavy paraffinic	Limit values (Belgium, 12/2023) [Olie] TWA 8 hours: 5 mg/m ³ . Form: mist. STEL 15 minutes: 10 mg/m ³ . Form: mist.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Limit values (Belgium, 12/2023) [Olie] TWA 8 hours: 5 mg/m ³ . Form: mist. STEL 15 minutes: 10 mg/m ³ . Form: mist.
naphthalene	Limit values (Belgium, 12/2023) Absorbed through skin. TWA 8 hours: 10 ppm. TWA 8 hours: 53 mg/m ³ . STEL 15 minutes: 15 ppm. STEL 15 minutes: 80 mg/m ³ . EU OEL (Europe, 1/2022) TWA 8 hours: 10 ppm. TWA 8 hours: 50 mg/m ³ .

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
 European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Result
Distillates (petroleum), hydrotreated light paraffinic	DNEL - General population - Long term - Oral 0.74 mg/kg bw/day <u>Effects</u> : Systemic DNEL - Workers - Long term - Dermal 0.97 mg/kg bw/day <u>Effects</u> : Systemic DNEL - General population - Long term - Inhalation 1.19 mg/m ³ <u>Effects</u> : Local DNEL - Workers - Long term - Inhalation

Q8 Auto 15 S

SECTION 8: Exposure controls/personal protection

	2.73 mg/m³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 5.58 mg/m³ <u>Effects</u> : Local
Distillates (petroleum), solvent-dewaxed heavy paraffinic	DNEL - General population - Long term - Oral 0.74 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.97 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.19 mg/m³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 2.73 mg/m³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 5.58 mg/m³ <u>Effects</u> : Local
Distillates (petroleum), hydrotreated heavy paraffinic	DNEL - General population - Long term - Oral 0.74 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.97 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.19 mg/m³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 2.73 mg/m³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 5.58 mg/m³ <u>Effects</u> : Local
2,6-di-tert-butylphenol	DNEL - General population - Long term - Oral 6.75 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Dermal 6.75 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 11.25 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 20.9 mg/m³ <u>Effects</u> : Systemic

Q8 Auto 15 S

SECTION 8: Exposure controls/personal protection

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol

DNEL - Workers - Long term - Inhalation

70.61 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

0.15 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.15 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.42 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.522 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

2.96 mg/m³

Effects: Systemic

3-((C9-11-iso,C10-rich)alkyloxy) propan-1-amine

DNEL - General population - Long term - Oral

0.25 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

0.25 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.7 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

0.74 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

4.9 mg/m³

Effects: Systemic

naphthalene

DNEL - Workers - Long term - Dermal

3.57 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Inhalation

25 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

25 mg/m³

Effects: Systemic

PNECs

Product/ingredient name

3-((C9-11-iso,C10-rich)alkyloxy) propan-1-amine

Result

Fresh water

0.0042 mg/l

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : ☒ Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : ☒ Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2. Gas and combination filter cartridges should comply with the European standard EN14387.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Oily liquid.]

Appearance : ☒ Clear

Color : ☒ Red

Odor : Hydrocarbon.

Odor threshold : Not available.

Melting point/freezing point : ☒ -42°C (<-43.6°F) [ASTM D 97]

Pour point : ☒ -42°C (<-43.6°F) [ASTM D 97]

Q8 Auto 15 S

SECTION 9: Physical and chemical properties

Boiling point or initial boiling point and boiling range	: >300°C (>572°F)
Flammability	: Not applicable.
Lower and upper explosion limit	: Not available.
Flash point	:  Open cup: >170°C (>338°F) [ASTM D 92]
Auto-ignition temperature	: >300°C (>572°F)
Decomposition temperature	: >300°C
pH	: Not applicable.
Viscosity	:  Kinematic (40°C (104°F)): 37.2 mm²/s (37.2 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 7.5 mm²/s (7.5 cSt) [ASTM D 445]

Solubility

Media	Result
 Water	Not soluble

Partition coefficient n-octanol/ water (log Pow) : Not applicable.

Vapor pressure	: <0.01 kPa (<0.075006 mm Hg)
Density	:  0.85 g/cm³ [15°C (59°F)] [ASTM D 4052]
Relative vapor density	: Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
Strong oxidizing materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Q8 Auto 15 S

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	
Product/ingredient name	Result
Distillates (petroleum), hydrotreated light paraffinic	Rat - Male, Female - Oral - LD50 >5000 mg/kg Rabbit - Male, Female - Dermal - LD50 >5000 mg/kg Acute Dermal Toxicity Rat - Inhalation - LC50 Dusts and mists 3900 mg/m³ [4 hours] Toxic effects: Behavioral - Tremor Lung, Thorax, or Respiration - Dyspnea Kidney, Ureter, and Bladder - Urine volume increased
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rabbit - Dermal - LD50 >5000 mg/kg Rat - Oral - LD50 >5000 mg/kg Rat - Male, Female - Inhalation - LC50 Dusts and mists 5.53 mg/l [4 hours] Acute Inhalation Toxicity
2,6-di-tert-butylphenol	Rabbit - Dermal - LD50 >10 g/kg Rat - Oral - LD50 1320 mg/kg
naphthalene	Rat - Oral - LD50 490 mg/kg Rabbit - Dermal - LD50 >20 g/kg

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	N/A	N/A	N/A	N/A	5.53
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	500	N/A	N/A	N/A	N/A
3-((C9-11-iso,C10-rich)alkyloxy) propan-1-amine	500	N/A	N/A	N/A	N/A
naphthalene	490	N/A	N/A	N/A	N/A

Skin corrosion/irritation

Product/ingredient name	Result
-------------------------	--------

Q8 Auto 15 S

SECTION 11: Toxicological information

Distillates (petroleum), hydrotreated light paraffinic	Rabbit - Skin - Erythema/Eschar <u>Duration of treatment/exposure:</u> 72 hours <u>Observation period:</u> 7 days <u>Irritation score:</u> 0.17 Fully reversible in 7 days or less
	Rabbit - Skin - Edema <u>Duration of treatment/exposure:</u> 72 hours <u>Observation period:</u> 7 days <u>Irritation score:</u> 0 Fully reversible in 7 days or less
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rabbit - Skin - Erythema/Eschar <u>Duration of treatment/exposure:</u> 72 hours <u>Observation period:</u> 7 days <u>Irritation score:</u> 0.17 Fully reversible in 7 days or less
	Rabbit - Skin - Edema <u>Duration of treatment/exposure:</u> 72 hours <u>Observation period:</u> 7 days <u>Irritation score:</u> 0 Fully reversible in 7 days or less
2,6-di-tert-butylphenol	Rat - Skin - Moderate irritant <u>Amount/concentration applied:</u> 0.5 MI
naphthalene	Rabbit - Skin - Mild irritant <u>Amount/concentration applied:</u> 495 mg
	Rabbit - Skin - Severe irritant <u>Duration of treatment/exposure:</u> 24 hours <u>Amount/concentration applied:</u> 0.05 MI

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name	Result
Distillates (petroleum), hydrotreated light paraffinic	Rabbit - Eyes - Iris lesion Acute Eye Irritation/Corrosion <u>Duration of treatment/exposure:</u> 48 hours <u>Observation period:</u> 72 hours <u>Irritation score:</u> 0 Fully reversible in 7 days or less
	Rabbit - Eyes - Redness of the conjunctivae Acute Eye Irritation/Corrosion <u>Duration of treatment/exposure:</u> 48 hours <u>Observation period:</u> 72 hours <u>Irritation score:</u> 0.33 Fully reversible in 7 days or less
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rabbit - Eyes - Iris lesion Acute Eye Irritation/Corrosion <u>Duration of treatment/exposure:</u> 48 hours <u>Observation period:</u> 72 hours <u>Irritation score:</u> 0 Fully reversible in 7 days or less
	Rabbit - Eyes - Redness of the conjunctivae Acute Eye Irritation/Corrosion

Q8 Auto 15 S

SECTION 11: Toxicological information

Duration of treatment/exposure: 48 hours
Observation period: 72 hours
Irritation score: 0.33
Fully reversible in 7 days or less

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation
Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Product/ingredient name

Distillates (petroleum), hydrotreated light paraffinic

Result

Guinea pig - skin
Skin Sensitization
Result: Not sensitizing

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Guinea pig - skin
Skin Sensitization
Result: Not sensitizing

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Product/ingredient name

Distillates (petroleum), hydrotreated light paraffinic

Result

In vivo - Mammalian-Animal - Somatic - Intraperitoneal
Mammalian Erythrocyte Micronucleus Test
Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

In vivo - Mammalian-Animal - Somatic - Intraperitoneal
Mammalian Erythrocyte Micronucleus Test
Result: Negative

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Product/ingredient name

Distillates (petroleum), hydrotreated light paraffinic

Result

Mouse - Female - Dermal - TC
Carcinogenicity Studies
78 weeks
Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Mouse - Female - Dermal - TC
Carcinogenicity Studies
78 weeks
Result: Negative

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Q8 Auto 15 S

SECTION 11: Toxicological information

Product/ingredient name

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result

Rat - Male, Female - Oral

Reproduction/Developmental Toxicity Screening Test
1000 mg/kg

Effects: No effect level.

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Rat - Male, Female - Oral

Reproduction/Developmental Toxicity Screening Test
1000 mg/kg

Effects: No effect level.

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result

ASPIRATION HAZARD - Category 1

ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Q8 Auto 15 S

SECTION 11: Toxicological information

Potential delayed effects : Not available.	
Potential chronic health effects	
Product/ingredient name	Result
Distillates (petroleum), hydrotreated light paraffinic	Sub-chronic - Rat - Male, Female - Oral - NOAEL Subchronic Dermal Toxicity: 90-day Study ≥2000 mg/kg [5 days per week] [13 weeks]
	Sub-acute - Rat - Male - Oral - LOAEL Repeated Dose 90-Day Oral Toxicity Study in Rodents 125 mg/kg [5 hours per day] [13 weeks]
	Sub-acute - Rat - Male - Inhalation - NOAEL >980 mg/m³ [5 days per week] [4 weeks]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Sub-chronic - Rat - Male, Female - Oral - NOAEL Subchronic Dermal Toxicity: 90-day Study ≥2000 mg/kg [5 days per week] [13 weeks]
	Sub-acute - Rat - Male - Oral - LOAEL Repeated Dose 90-Day Oral Toxicity Study in Rodents 125 mg/kg [5 hours per day] [13 weeks]
	Sub-acute - Rat - Male - Inhalation - NOAEL >980 mg/m³ [5 days per week] [4 weeks]
Conclusion/Summary [Product] : Not available.	
General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards
11.2.1 Endocrine disrupting properties

Not available.	
Conclusion/Summary [Product]	: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information
Not available.

SECTION 12: Ecological information

12.1 Toxicity	
Product/ingredient name	Result
((C9-11-iso,C10-rich)alkyloxy) propan-1-amine	Acute - EC50 Algae 0.0544 mg/l [72 hours]
	Acute - LC50 Fish 2.14 mg/l [96 hours]
	Chronic - EC10 Algae 0.0421 mg/l [72 hours]
	Chronic - EC10 Daphnia 0.738 mg/l [21 days]

Q8 Auto 15 S

SECTION 12: Ecological information

naphthalene	Acute - EC50 - Fresh water Daphnia - Water flea - <i>Daphnia magna</i> - Neonate <u>Age</u>: ≤24 hours 1.6 mg/l [48 hours] <u>Effect</u>: Intoxication Acute - LC50 - Fresh water Fish - Crimson-spotted rainbowfish - <i>Melanotaenia fluviatilis</i> - Larvae <u>Age</u>: 1 days 213 µg/l [96 hours] <u>Effect</u>: Mortality Chronic - NOEC - Fresh water Fish - Mozambique tilapia - <i>Oreochromis mossambicus</i> <u>Age</u>: 4 months; <u>Size</u>: 5.4 cm; <u>Weight</u>: 5.5 g 1.5 mg/l [60 days] <u>Effect</u>: Growth Chronic - NOEC - Marine water Crustaceans - Fiddler crab - <i>Uca pugnax</i> - Adult <u>Size</u>: 12.7 to 21.4 mm 0.5 mg/l [3 weeks] <u>Effect</u>: Growth
-------------	---

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name	Result
3-((C9-11-iso,C10-rich)alkyloxy) propan-1-amine	OECD 301D [Ready Biodegradability - Closed Bottle Test] 68% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated light paraffinic	-	-	Inherent
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Inherent
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Inherent
3-((C9-11-iso,C10-rich) alkyloxy) propan-1-amine	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Distillates (petroleum), hydrotreated light paraffinic	>3	-	Low
Distillates (petroleum), solvent-dewaxed heavy paraffinic	>3	-	Low
Distillates (petroleum), hydrotreated heavy paraffinic	>1	-	Low
2,6-di-tert-butylphenol	4.5	-	High
2,2'-(C16-18 (evennumbered, C18	3.6	-	Low

Q8 Auto 15 S

SECTION 12: Ecological information

unsaturated) alkyl imino) diethanol naphthalene	3.4	36.5 to 168 [OECD 305]	Low
---	-----	------------------------	-----

12.4 Mobility in soil

Soil/Water partition coefficient

Product/ingredient name	logKoc	Koc
2,6-di-tert-butylphenol naphthalene	3.5 3	3181.17 913.843

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No	No
2,6-di-tert-butylphenol	No	No	No	No	No	No	No
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	No	No	No	No	No	No	No
3-((C9-11-iso,C10-rich) alkyloxy) propan-1-amine	No	No	No	No	No	No	No
naphthalene	No	No	No	No	No	No	No

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Distillates (petroleum), hydrotreated light paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
2,6-di-tert-butylphenol	No	N/A	N/A	No	N/A	N/A	N/A
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	No	N/A	N/A	No	N/A	N/A	N/A
3-((C9-11-iso,C10-rich) alkyloxy) propan-1-amine	No	N/A	N/A	No	N/A	N/A	N/A
naphthalene	No	N/A	No	No	No	N/A	No

Regulation (EC) No. 1272/2008 [CLP]

Q8 Auto 15 S

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No	No
2,6-di-tert-butylphenol	No	No	No	No	No	No	No
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	No	No	No	No	No	No	No
3-((C9-11-iso,C10-rich) alkyloxy) propan-1-amine	No	No	No	No	No	No	No
naphthalene	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Q8 Auto 15 S

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization
Annex XIV

None of the components are listed.

Substances of very high concern
None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
☒ Q8 Auto 15 S	≥90	3

Labeling : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : ☒ Not applicable.

Ozone depleting substances (EU 2024/590)
Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Q8 Auto 15 S

SECTION 15: Regulatory information

Not listed.

Persistent Organic Pollutants (1021/2019/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
hydrocarbures polycycliques aromatiques	Listed

Germany

Hazard class for water (WGK) : 3

Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: Not determined.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: Not determined.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: Not determined.
United States of America	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ASTM = American Society for Testing and Materials
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DIN = German Institute for Standardization
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EC = European Commission
 EC50 = Half maximal effective concentration
 EN = European Standard (Norm)
 EUH statement = CLP-specific Hazard statement
 GHS - Globally Harmonized System of Classification and Labeling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IC50 = Half maximal inhibitory concentration
 IMDG = International Maritime Dangerous Goods
 IMO = International Maritime Organisation
 ISO = International Organization for Standardization
 LC50 = Median lethal concentration
 LD50 = Median lethal dose
 LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration
 NOEL / NOEC = No Observed Effect Level / Concentration
 OECD = Organisation for Economic Co-operation and Development
 OEL = Occupational Exposure Limit
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS = Safety Data Sheet
 SVHC = Substances of Very High Concern
 STEL = Short Term Exposure Limit
 TLV = Threshold Limit Value
 TWA = Time Weighted Average
 UFI = Unique Formula Identifier
 UN = United Nations
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Q8 Auto 15 S

SECTION 16: Other information

Full text of abbreviated H statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2

Training advice : Ensure operatives are trained to minimise exposures.

Date of printing : 02-10-2025

Date of issue/ Date of revision : 02-10-2025

Date of previous issue : 09-05-2023

Version : 1.08

Prepared by : Kuwait Petroleum Research & Technology B.V., The Netherlands

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.