

Q8 Gear Oil M LD 75W-80

Full synthetic long drain transmission fluid for MAN

Description

Q8 Gear Oil M LD 75W-80 is a superior fully synthetic transmission fluid, offering extended drain intervals up to 1 mio. km and best-in-class performance in demanding conditions. This product provides easy gear shifting and exceptional protection in high temperature conditions due to constant film strength. Low viscosity characteristics optimize transmission efficiency and fuel economy.

Applications

Q8 Gear Oil M LD 75W-80 is especially designed for MAN GA2/GB and Scania STO MTF for long drain intervals. This product meets the requirements of many commercial vehicle OEMs and/or gearbox manufacturers including ZF, DAF, IVECO, Eaton.

Benefits

- Outstanding drain interval extension.
- Best-in-class oxidation stability.
- Improved fuel economy.
- Full synthetic formulation technology for highest durability
- Outstanding oil film strength.

Specifications / Recommendations / Approvals

API	GL-4	MAN	341 Type Z5
MAN	341 Type GA2	Scania	STO MTF
MAN	341 Type GB		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,864
Viscosity Grade	SAE J306	SAE	75W-80
Kinematic Viscosity, 100 °C	D 445	mm ² /s	10.0
Kinematic Viscosity, 40 °C	D 445	mm ² /s	61.4
Viscosity Index	D 2270	-	151
Brookfield Viscosity, -40 °C	D 2983	Pa.s	20.0
Flash Point, COC	D 92	°C	239
Pour Point	D 97	°C	-58

The figures above are not a specification. They are typical figures obtained within production tolerances.