

Q8 Bach XNRG 25

Extreme performance neat cutting oil

Description

Q8 Bach XNRG 25 is based on renewable esters which are readily biodegradable. Formulated as non-active neat cutting fluid, free from chlorine and suitable for the machining of a wide range of materials. These include cast iron, carbon steel, high alloy steels, stainless steel, heat resistant alloys, aluminium, copper and copper alloys. This synthetic product has a high flash point in comparison to mineral oil based products, which in combination with low foaming and the selected extreme performance additives, results in a human exposure friendly product with an extreme good oxidation stability.

Applications

Primarily designed for general machining and broaching, the product is also well-suited for a wide range of operations, including severe machining and applications requiring high load capability. For certain processes, machining with MQL is also a viable option. Its exceptionally long tool life and superior surface finish help reduce manufacturing costs and minimize rework.

User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from water entry, frost and direct sunlight.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,890
Kinematic Viscosity, 40 °C	D 445	mm ² /s	23
Flash Point, COC	D 92	°C	205
Colour	D 1500	-	1.0
Copper Strip, 3 h, 100 °C	D 130	-	1a
Four Ball Test, Weld Load	IP 239	kg	440

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.