

Q8 Bach XNRG 32

Extreme performance neat cutting oil

Description

Q8 Bach XNRG 32 is based on renewable esters which are readily biodegradable. Formulated as non-active neat cutting fluid, free from chlorine and suitable for the machining of a wide range of materials. These include cast iron, carbon steel, high alloy steels, stainless steel, heat resistant alloys, aluminium, copper and copper alloys. This synthetic product has a high flash point in comparison to mineral oil based products, which in combination with low foaming and the selected extreme performance additives, results in a human exposure friendly product with an extreme good oxidation stability.

Applications

Primair ontworpen voor algemene bewerkingen en broachen, maar het product is ook zeer geschikt voor een breed scala aan toepassingen, waaronder zwaar verspanen en bewerkingen met hoge belasting. Voor bepaalde processen is bewerken met MQL eveneens een haalbare optie. De uitzonderlijk lange standtijd en superieure oppervlakteafwerking helpen de productiekosten te verlagen en nabewerkingen te minimaliseren. Q8 Bach XNRG 32 is ook geschikt voor algemene machine-smering.

User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from water entry, frost and direct sunlight.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,913
Density, 20 °C	D 4052	g/ml	0,909
Kinematic Viscosity, 40 °C	D 445	mm ² /s	32
Flash Point, COC	D 92	°C	240
Colour	D 1500	-	2.5
Copper Strip, 3 h, 100 °C	D 130	-	1a
Four Ball Test, Weld Load	IP 239	kg	380

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Bach XNRG 32 is **2.09** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

