

Q8 Formula Elite FPW 5W-30

Synthetic passenger car engine oil

Description

Q8 Formula Elite FPW 5W-30 is a superior performance passenger car engine oil. This product delivers superior protection against engine wear and sludge formation, extends drain intervals and is compatible with aftertreatment systems. Q8 Formula Elite FPW 5W-30 has passed the official Stellantis engine test for FPW9.55535/03 (v1)

Applications

Q8 Formula Elite FPW 5W-30 is especially developed for Stellantis engines and suitable for passenger cars and commercial vehicles with normally aspirated or turbocharged gasoline, LPG or diesel Euro 5 and 6 engines requiring a mid SAPS engine oil. Q8 Formula Elite FPW 5W-30 has passed the official Stellantis engine test for FPW 9.55535/03 (V1)

Benefits

- Outstanding engine cleanliness increasing engine durability.
- Superb protection for exhaust catalyst and diesel particulate filter.
- Fuel economy improvement of 1% or more
- Offers moderate oil drain interval extention
- Outstanding engine protection after cold starting.

Specifications, recommendations and approvals

Stellantis FPW 9.55535-03 (V1)

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,852
Viscosity Grade	SAE J300	SAE	5W-30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	71,5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11,9
Viscosity Index	D 2270	-	162
Apparent Viscosity, -30 °C	D 5293	mPa.s	5800
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	230
Sulfated Ash	D 874	% mass	0,8

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Formula Elite FPW 5W-30 is 1.56 kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



we
take
care

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

