

Q8 Garden Pro 4T SAE 30

Advanced garden oil

Description

Q8 Garden Pro 4T SAE 30 is an advanced monograde mineral oil that meets the requirements of several small engines used in garden equipment. Its components are carefully selected which results in a high protection against rust, wear and oxidation. Q8 Garden Pro 4T SAE 30 guarantees an optimum cleanliness thanks to the strong deposit control. This garden oil has a high thermal and mechanical stability.

Applications

Q8 Garden Pro 4T SAE 30 is used in several 4-stroke gasoline engines of garden equipment such as lawn mowers, rider mowers and snow blowers.

Benefits

- High oil film strength preventing engine wear.
- High protection against rust and corrosion.
- Optimum protection against piston ring-sticking and varnish deposits.

Specifications, recommendations and approvals

API CD API SF

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,881
Viscosity Grade	-	-	SAE 30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	86,9
Viscosity Index	D 2270	-	112
Pour Point	D 97	°C	-27

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Garden Pro 4T SAE 30 is **1.99** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check here



**we
take
care**

PRODUCT CARBON FOOTPRINT
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:
ISO 14067 | ATIEL-UEIL PCF

