

## Q8 Garden Pro Synt 4T 5W-30

Superior garden oil

### Description

Q8 Garden Pro Synt 4T 5W-30 is a superior synthetic multigrade lubricant for garden equipment. It guarantees an exceptional performance in both air and water cooled engines. Q8 Garden Pro Synt 4T 5W-30 has been enriched with unique components that improve lubricity and enhance detergency and cleanliness. The reliable garden oil offers an extreme wear protection.

### Applications

Q8 Garden Pro Synt 4T 5W-30 is used in all 4-stroke gasoline engines of garden equipment such as lawn mowers, rider mowers and snow blowers. It is a reliable lubricant that covers a broad range of applications and can be used in the most severe conditions.

### Specifications, recommendations and approvals

ACEA	A3/B4	MB	229.1
API	CF	VAG	VW 502.00
API	SL		

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,851
Viscosity Grade	-	-	5W-30
Kinematic Viscosity, 40 °C	ISO 3104	mm <sup>2</sup> /s	64.3
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	11.3
Viscosity Index	D 2270	-	169
Apparent Viscosity, -30 °C	D 5293	mPa.s	4300
Flash Point, P-M	D 93	°C	237
Pour Point	D 97	°C	-36
Sulfated Ash	D 874	% mass	1.2

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Garden Pro Synt 4T 5W-30 is 1.34 kg CO<sub>2</sub>eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

To ensure accuracy and reliability, the PCF calculation tool has been verified by an independent third party. The verification report is available in the disclaimer.

For more info check [here](#)



we  
take  
care

PRODUCT CARBON FOOTPRINT  
METHOD VALIDATED BY:

PCF CALCULATION IN LINE WITH:  
ISO 14067 | ATIEL-UEIL PCF

