

SAFETY DATA SHEET

Q8 Verdi 22



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Q8 Verdi 22
Viscosity or Type : ISO VG 22

1.2 Relevant identified uses of the substance or mixture and uses advised against

Material uses : Lubricating oil for industrial systems

1.3 Details of the supplier of the safety data sheet

Supplier : Kuwait Petroleum Companies in the Benelux
Company Office: Desguinlei 100 - 8, 2018 Antwerp, Belgium
Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium
Tel. +32 3 247 38 11, Fax +32 3 216 03 42

Manufacturer / Distributor : Kuwait Petroleum Belgium N.V./S.A. / Q8Oils Italia S.r.l.
Petroleumkaai 7
B-2020 Antwerp
Belgium
Via Volpedo 2
15050 Castellar Guidobono (AL)
Italy

e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only.

PCN Information contact : PCNinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Europe : +44 (0) 1235 239 670
Global (English only) : +44 (0) 1865 407 333



National advisory body/Poison Center

Belgium : Poison Centre : +32 (0)70 245 245

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

AQUATIC HAZARD (LONG-TERM) Category 3 H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity : None.

Ingredients of unknown ecotoxicity : None.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P273 - Avoid release to the environment.

Response : Not applicable.

SECTION 2: Hazards identification

| | |
|---|--|
| Storage | : Not applicable. |
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | : <input checked="" type="checkbox"/> Not applicable. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable. |
| <u>Special packaging requirements</u> | |
| Containers to be fitted with child-resistant fastenings | : Not applicable. |
| Tactile warning of danger | : Not applicable. |

2.3 Other hazards

| | |
|--|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : Prolonged or repeated contact may dry skin and cause irritation. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|--|--|------|---|---|---------|
| Severely refined mineral oil (C15 - C50) * - Not classified. | - | ≥90 | Not classified. | - | [2] |
| 2,6-di-tert-butylphenol | REACH #: 01-2119490822-33 EC: 204-884-0 CAS: 128-39-2 | <1 | Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M [Acute] = 1 M [Chronic] = 1 | [1] |
| Severely refined mineral oil (C15 - C50) * - H304 | - | ≤0.3 | Asp. Tox. 1, H304 | - | [1] [2] |
| Distillates (petroleum), hydrotreated light naphthenic | REACH #: 01-2119480375-34 EC: 265-156-6 CAS: 64742-53-6 Index: 649-466-00-2 | ≤0.1 | Asp. Tox. 1, H304 | - | [1] [2] |
| | | | See Section 16 for the full text of the H statements declared above. | | |

* Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25

CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29

CAS: 64742-56-9, EC: 265-159-2, EU REACH: 01-2119480132-48

CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27

SECTION 3: Composition/information on ingredients

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact

: No specific data.

Inhalation

: No specific data.

Skin contact

: Adverse symptoms may include the following:
irritation
dryness
cracking

Ingestion

: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|--|--|
| Severely refined mineral oil (C15 - C50) * - Not classified. | EU OEL (Europe) TWA 8 hours: 5 mg/m ³ . Form: Mist. STEL 15 minutes: 10 mg/m ³ . Form: Mist. |
| Severely refined mineral oil (C15 - C50) * - H304 | EU OEL (Europe) TWA 8 hours: 5 mg/m ³ . Form: Mist. STEL 15 minutes: 10 mg/m ³ . Form: Mist. |
| White mineral oil (petroleum) | Limit values (Belgium, 12/2023) [Olie] TWA 8 hours: 5 mg/m ³ . Form: mist. STEL 15 minutes: 10 mg/m ³ . Form: mist. |
| Distillates (petroleum), hydrotreated light naphthenic | Limit values (Belgium, 12/2023) [Olie] TWA 8 hours: 5 mg/m ³ . Form: mist. STEL 15 minutes: 10 mg/m ³ . Form: mist. EU OEL (Europe) TWA: 5 mg/m ³ (oil Mist). |

Biological exposure indices

No exposure indices known.

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

2,6-di-tert-butylphenol

Result

DNEL - General population - Long term - Oral

6.75 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Dermal

6.75 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

11.25 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

20.9 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

70.61 mg/m³

Effects: Systemic

DNEL - General population - Long term - Oral

0.74 mg/kg bw/day

Effects: Systemic

DNEL - Workers - Long term - Dermal

0.97 mg/kg bw/day

Effects: Systemic

DNEL - General population - Long term - Inhalation

1.19 mg/m³

Effects: Local

DNEL - Workers - Long term - Inhalation

2.73 mg/m³

Effects: Systemic

DNEL - Workers - Long term - Inhalation

5.58 mg/m³

Effects: Local

Distillates (petroleum), hydrotreated light naphthenic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

SECTION 8: Exposure controls/personal protection

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2. Gas and combination filter cartridges should comply with the European standard EN14387.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Oily liquid.]

Appearance : Clear

Color : Yellow [Light]

Odor : Characteristic

Odor threshold : Not available.

Melting point/freezing point : Not applicable.

Pour point : 30°C (-22°F) [ASTM D 97]

Boiling point or initial boiling point and boiling range : >300°C (>572°F)

Flammability : Not applicable.

Lower and upper explosion limit : Not available.

SECTION 9: Physical and chemical properties

| | |
|----------------------------------|--|
| Flash point | : Open cup: 200°C (392°F) [ASTM D 92] |
| Auto-ignition temperature | : >300°C (>572°F) |
| Decomposition temperature | : >300°C |
| pH | : Not applicable. |
| Viscosity | : Kinematic (40°C (104°F)): 22 mm ² /s (22 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 4.3 mm ² /s (4.3 cSt) [ASTM D 445] |
| Solubility | : |
| Media | Result |
| Water | Not soluble |

Partition coefficient n-octanol/water (log Pow) : Not applicable.

| | |
|---------------------------------|---|
| Vapor pressure | : <0.01 kPa (<0.075006 mm Hg) |
| Density | : 0.86 g/cm ³ [15°C (59°F)] [ASTM D 4052] |
| Relative vapor density | : Not available. |
| Particle characteristics | |

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

| | |
|-----------------------------|-------------------|
| Explosive properties | : Not applicable. |
| Oxidizing properties | : Not applicable. |

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

| | |
|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : No specific data. |
| 10.5 Incompatible materials | : Reactive or incompatible with the following materials: Strong oxidizing materials |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result |
|-------------------------|--------|
|-------------------------|--------|

SECTION 11: Toxicological information

| | |
|---|---|
| Severely refined mineral oil (C15 - C50) * - Not classified. | Rabbit - Dermal - LD50 >5000 mg/kg |
| | Rat - Oral - LD50 >5000 mg/kg |
| | Rat - Male, Female - Inhalation - LC50 Dusts and mists 5.53 mg/l [4 hours] Acute Inhalation Toxicity |
| 2,6-di-tert-butylphenol | Rabbit - Dermal - LD50 >10 g/kg |
| | Rat - Oral - LD50 1320 mg/kg |
| Severely refined mineral oil (C15 - C50) * - H304 | Rabbit - Dermal - LD50 >5000 mg/kg |
| | Rat - Oral - LD50 >5000 mg/kg |
| | Rat - Male, Female - Inhalation - LC50 Dusts and mists 5.53 mg/l [4 hours] Acute Inhalation Toxicity |
| Distillates (petroleum), hydrotreated light naphthenic | Rat - Oral - LD50 >5000 mg/kg <u>Toxic effects:</u> Behavioral - Somnolence (general depressed activity) |
| | Rat - Inhalation - LC50 Dusts and mists 2180 mg/m ³ [4 hours] <u>Toxic effects:</u> Lung, Thorax, or Respiration - Structural or functional change in trachea or bronchi |

Conclusion/Summary [Product] : Not toxic.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| Severely refined mineral oil (C15 - C50) * - Not classified. | N/A | N/A | N/A | N/A | 5.53 |
| Severely refined mineral oil (C15 - C50) * - H304 | N/A | N/A | N/A | N/A | 5.53 |

Skin corrosion/irritation

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
Not classified.

Result

Rabbit - Skin - Erythema/Eschar

Duration of treatment/exposure: 72 hours

Observation period: 7 days

Irritation score: 0.17

Fully reversible in 7 days or less

Rabbit - Skin - Edema

Duration of treatment/exposure: 72 hours

Observation period: 7 days

Irritation score: 0

Fully reversible in 7 days or less

SECTION 11: Toxicological information

2,6-di-tert-butylphenol

Rat - Skin - Moderate irritant

Amount/concentration applied: 0.5 MI

Severely refined mineral oil (C15 - C50) * -
H304

Rabbit - Skin - Erythema/Eschar

Duration of treatment/exposure: 72 hours

Observation period: 7 days

Irritation score: 0.17

Fully reversible in 7 days or less

Rabbit - Skin - Edema

Duration of treatment/exposure: 72 hours

Observation period: 7 days

Irritation score: 0

Fully reversible in 7 days or less

Conclusion/Summary [Product] : Non-irritant to skin.

Serious eye damage/eye irritation

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
Not classified.

Result

Rabbit - Eyes - Iris lesion

Acute Eye Irritation/Corrosion

Duration of treatment/exposure: 48 hours

Observation period: 72 hours

Irritation score: 0

Fully reversible in 7 days or less

Rabbit - Eyes - Redness of the conjunctivae

Acute Eye Irritation/Corrosion

Duration of treatment/exposure: 48 hours

Observation period: 72 hours

Irritation score: 0.33

Fully reversible in 7 days or less

Severely refined mineral oil (C15 - C50) * -
H304

Rabbit - Eyes - Iris lesion

Acute Eye Irritation/Corrosion

Duration of treatment/exposure: 48 hours

Observation period: 72 hours

Irritation score: 0

Fully reversible in 7 days or less

Rabbit - Eyes - Redness of the conjunctivae

Acute Eye Irritation/Corrosion

Duration of treatment/exposure: 48 hours

Observation period: 72 hours

Irritation score: 0.33

Fully reversible in 7 days or less

Conclusion/Summary [Product] : Non-irritating to the eyes.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Non-irritant to lungs.

Respiratory or skin sensitization

Product/ingredient name

Result

SECTION 11: Toxicological information

Severely refined mineral oil (C15 - C50) * -
Not classified.

Guinea pig - skin
Skin Sensitization
Result: Not sensitizing

Severely refined mineral oil (C15 - C50) * -
H304

Guinea pig - skin
Skin Sensitization
Result: Not sensitizing

Skin

Conclusion/Summary [Product] : Not sensitizing

Respiratory

Conclusion/Summary [Product] : Not classified for respiratory sensitization.

Germ cell mutagenicity

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
Not classified.

Result

In vivo - Mammalian-Animal - Somatic - Intraperitoneal
Mammalian Erythrocyte Micronucleus Test
Result: Negative

Severely refined mineral oil (C15 - C50) * -
H304

In vivo - Mammalian-Animal - Somatic - Intraperitoneal
Mammalian Erythrocyte Micronucleus Test
Result: Negative

Conclusion/Summary [Product] : No mutagenic effect.

Carcinogenicity

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
Not classified.

Result

Mouse - Female - Dermal - TC
Carcinogenicity Studies
78 weeks
Result: Negative

Severely refined mineral oil (C15 - C50) * -
H304

Mouse - Female - Dermal - TC
Carcinogenicity Studies
78 weeks
Result: Negative

Conclusion/Summary [Product] : No carcinogenic effect.

Reproductive toxicity

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
Not classified.

Result

Rat - Male, Female - Oral
Reproduction/Developmental Toxicity Screening Test
1000 mg/kg
Effects: No effect level.
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Severely refined mineral oil (C15 - C50) * -
H304

Rat - Male, Female - Oral
Reproduction/Developmental Toxicity Screening Test
1000 mg/kg
Effects: No effect level.
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

SECTION 11: Toxicological information

Conclusion/Summary [Product] : No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
H304
Distillates (petroleum), hydrotreated light
naphthenic

Result

ASPIRATION HAZARD - Category 1
ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
Not classified.

Result

Sub-chronic - Rat - Male, Female - Oral - NOAEL
Subchronic Dermal Toxicity: 90-day Study
≥2000 mg/kg [5 days per week] [13 weeks]

Sub-acute - Rat - Male - Oral - LOAEL

Repeated Dose 90-Day Oral Toxicity Study in Rodents
125 mg/kg [5 hours per day] [13 weeks]

Sub-acute - Rat - Male - Inhalation - NOAEL

>980 mg/m³ [5 days per week] [4 weeks]

Severely refined mineral oil (C15 - C50) * -
H304

Sub-chronic - Rat - Male, Female - Oral - NOAEL
Subchronic Dermal Toxicity: 90-day Study

SECTION 11: Toxicological information

≥2000 mg/kg [5 days per week] [13 weeks]

Sub-acute - Rat - Male - Oral - LOAEL

Repeated Dose 90-Day Oral Toxicity Study in Rodents
125 mg/kg [5 hours per day] [13 weeks]

Sub-acute - Rat - Male - Inhalation - NOAEL

>980 mg/m³ [5 days per week] [4 weeks]

Conclusion/Summary [Product] : Not toxic.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

Severely refined mineral oil (C15 - C50) * -
Not classified.

Result

Acute - NEL - Fresh water
Fish, Acute Toxicity Test
Fish - *Pimephales promelas*
≥100 mg/l [96 hours]

Acute - NEL - Fresh water
Daphnia sp. Acute Immobilization Test and Reproduction Test
Daphnia - *Daphnia Magma*
>10000 mg/l [48 hours]

Chronic - NEL - Fresh water
Daphnia Magna Reproduction Test
Daphnia - *Daphnia magna*
10 mg/l [21 days]
Effect: Reproduction

Acute - NEL - Fresh water
Alga, Growth Inhibition Test
Algae
>100 mg/l [72 hours]
Effect: (growth rate)

Severely refined mineral oil (C15 - C50) * -
H304

Acute - NEL - Fresh water
Fish, Acute Toxicity Test
Fish - *Pimephales promelas*
≥100 mg/l [96 hours]

Acute - NEL - Fresh water
Daphnia sp. Acute Immobilization Test and Reproduction Test
Daphnia - *Daphnia Magma*
>10000 mg/l [48 hours]

SECTION 12: Ecological information

Chronic - NEL - Fresh water

Daphnia Magna Reproduction Test

Daphnia - *Daphnia magna*

10 mg/l [21 days]

Effect: Reproduction

Acute - NEL - Fresh water

Alga, Growth Inhibition Test

Algae

>100 mg/l [72 hours]

Effect: (growth rate)

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|--|-------------------|------------|------------------|
| Severely refined mineral oil (C15 - C50) * - Not classified. | - | - | Inherent |
| Severely refined mineral oil (C15 - C50) * - H304 | - | - | Inherent |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| 2,6-di-tert-butylphenol | 4.5 | - | High |

12.4 Mobility in soil

Soil/Water partition coefficient

| Product/ingredient name | logK _{oc} | K _{oc} |
|-------------------------|--------------------|-----------------|
| 2,6-di-tert-butylphenol | 3.5 | 3181.17 |

Results of PMT and vPvM assessment

| Product/ingredient name | PMT | P | M | T | vPvM | vP | vM |
|--|-----|----|----|----|------|----|----|
| Severely refined mineral oil (C15 - C50) * - Not classified. | No | No | No | No | No | No | No |
| 2,6-di-tert-butylphenol | No | No | No | No | No | No | No |
| Severely refined mineral oil (C15 - C50) * - H304 | No | No | No | No | No | No | No |
| Distillates (petroleum), hydrotreated light naphthenic | No | No | No | No | No | No | No |

Mobility : Not available.

Conclusion/Summary : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

SECTION 12: Ecological information

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|--|-----|-----|-----|----|------|-----|-----|
| Severely refined mineral oil (C15 - C50) * - Not classified. | No | N/A | N/A | No | N/A | N/A | N/A |
| 2,6-di-tert-butylphenol | No | N/A | N/A | No | N/A | N/A | N/A |
| Severely refined mineral oil (C15 - C50) * - H304 | No | N/A | N/A | No | N/A | N/A | N/A |
| Distillates (petroleum), hydrotreated light naphthenic | No | N/A | N/A | No | N/A | N/A | N/A |

Regulation (EC) No. 1272/2008 [CLP]

| Product/ingredient name | PBT | P | B | T | vPvB | vP | vB |
|--|-----|----|----|----|------|----|----|
| Severely refined mineral oil (C15 - C50) * - Not classified. | No | No | No | No | No | No | No |
| 2,6-di-tert-butylphenol | No | No | No | No | No | No | No |
| Severely refined mineral oil (C15 - C50) * - H304 | No | No | No | No | No | No | No |
| Distillates (petroleum), hydrotreated light naphthenic | No | No | No | No | No | No | No |

Conclusion/Summary

Regulation (EC) No. 1272/2008 [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 13 02 05* | mineral-based non-chlorinated engine, gear and lubricating oils |

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name | % | Designation [Usage] |
|-------------------------|-----|---------------------|
| Q8 Verdi 22 | ≥90 | 3 |

Labeling : Not applicable.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) -

Air

SECTION 15: Regulatory information

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants (1021/2019/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Germany

Hazard class for water : 1
(WGK)

Switzerland

VOC content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

| | |
|---------------------------------|--|
| Australia | : Not determined. |
| Canada | : Not determined. |
| China | : Not determined. |
| Eurasian Economic Union | : Russian Federation inventory: Not determined. |
| Japan | : Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. |
| New Zealand | : Not determined. |
| Philippines | : Not determined. |
| Republic of Korea | : Not determined. |
| Taiwan | : Not determined. |
| Thailand | : Not determined. |
| Turkey | : Not determined. |
| United States of America | : Not determined. |
| Viet Nam | : Not determined. |

SECTION 15: Regulatory information

15.2 Chemical Safety Assessment : Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

▼ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM = American Society for Testing and Materials
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DIN = German Institute for Standardization
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EC = European Commission
EC50 = Half maximal effective concentration
EN = European Standard (Norm)
EUH statement = CLP-specific Hazard statement
GHS - Globally Harmonized System of Classification and Labeling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IC50 = Half maximal inhibitory concentration
IMDG = International Maritime Dangerous Goods
IMO = International Maritime Organisation
ISO = International Organization for Standardization
LC50 = Median lethal concentration
LD50 = Median lethal dose
LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration
NOEL / NOEC = No Observed Effect Level / Concentration
OECD = Organisation for Economic Co-operation and Development
OEL = Occupational Exposure Limit
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS = Safety Data Sheet
SVHC = Substances of Very High Concern
STEL = Short Term Exposure Limit
TLV = Threshold Limit Value
TWA = Time Weighted Average
UFI = Unique Formula Identifier
UN = United Nations
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|--------------------|
| Aquatic Chronic 3, H412 | Calculation method |

SECTION 16: Other information

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

| | |
|------|---|
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

Full text of classifications [CLP/GHS]

| | |
|-------------------|---|
| Aquatic Acute 1 | AQUATIC HAZARD (ACUTE) - Category 1 |
| Aquatic Chronic 1 | AQUATIC HAZARD (LONG-TERM) - Category 1 |
| Aquatic Chronic 3 | AQUATIC HAZARD (LONG-TERM) - Category 3 |
| Asp. Tox. 1 | ASPIRATION HAZARD - Category 1 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |

Training advice : Ensure operatives are trained to minimise exposures.

Date of printing : 19-01-2026

Date of issue/ Date of revision : 19-01-2026

Date of previous issue : 09-11-2022

Version : 1.06

Prepared by : Kuwait Petroleum Research & Technology B.V., The Netherlands

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.